



PRODUCT-DETAILS

# CL-100C

## CL-100C Pilot Light



| General Information   |                                                                                                                                                                                                                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CL-100C                                                                                                                                                                                                                                                                                                           |
| Product ID            | 1SFA619402R1008                                                                                                                                                                                                                                                                                                   |
| EAN                   | 7320500555873                                                                                                                                                                                                                                                                                                     |
| Catalog Description   | CL-100C Pilot Light                                                                                                                                                                                                                                                                                               |
| Long Description      | The CL-100C Pilot Light is: Compact - Pilot Light - Pilot light head - Clear - Illuminated - 240 V<br>This Pilot Light is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.<br>The compact range has a high level of dust and water resistance. |

| Ordering               |            |
|------------------------|------------|
| Minimum Order Quantity | 10 piece   |
| Customs Tariff Number  | 8536619090 |

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals          | 1SFC151011M0201 |

Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 0.03 m   |
| Product Net Height         | 0.03 m   |
| Product Net Depth / Length | 0.055 m  |
| Product Net Weight         | 0.018 kg |

Technical

|                                                   |                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                           | Operation -25 ... +70 °C<br>Storage -40 ... +85 °C                                                                                                                                                                                                                                                                         |
| Color                                             | Clear                                                                                                                                                                                                                                                                                                                      |
| Actuator Type                                     | Pilot light head                                                                                                                                                                                                                                                                                                           |
| Bezel Material                                    | n/a                                                                                                                                                                                                                                                                                                                        |
| Illumination                                      | Illuminated                                                                                                                                                                                                                                                                                                                |
| Lamp Type                                         | Ba9s                                                                                                                                                                                                                                                                                                                       |
| Enclosure Type NEMA                               | Type1<br>Type12<br>Type13<br>Type3R<br>Type4<br>Type4X                                                                                                                                                                                                                                                                     |
| Pollution Degree                                  | 3                                                                                                                                                                                                                                                                                                                          |
| Rated Frequency (f)                               | Supply Circuit 50 60 Hz                                                                                                                                                                                                                                                                                                    |
| Rated Operational Voltage                         | Maximum 240 V                                                                                                                                                                                                                                                                                                              |
| Rated Operational Current DC-13 (I <sub>θ</sub> ) | (24 V) 0.3 A<br>(125 V) 0.2 A                                                                                                                                                                                                                                                                                              |
| Rated Operational Current AC-15 (I <sub>θ</sub> ) | (24 / 127 V) 1.5 A<br>(220 / 240 V) 1 A                                                                                                                                                                                                                                                                                    |
| Connecting Capacity                               | Flexible with Ferrule 1 x 0.75...2.5 mm²<br>Flexible with Ferrule 2 x 0.75...2.5 mm²<br>Flexible with Insulated Ferrule 1 x 0.75...2.5 mm²<br>Flexible with Insulated Ferrule 2 x 0.75...2.5 mm²<br>Flexible 1 x 0.75 ... 2.5 mm²<br>Flexible 2 x 0.75 ... 2.5 mm²<br>Solid 1 x 0.75...2.5 mm²<br>Solid 2 x 0.75...2.5 mm² |
| Connection Type                                   | Screw Clamp                                                                                                                                                                                                                                                                                                                |
| Terminal Type                                     | Screw Terminals                                                                                                                                                                                                                                                                                                            |
| Tightening Torque                                 | 0.9 N·m                                                                                                                                                                                                                                                                                                                    |
| Wire Stripping Length                             | 8 mm                                                                                                                                                                                                                                                                                                                       |
| Suitable For                                      | Bulb 3W max.                                                                                                                                                                                                                                                                                                               |
| Suitable for Product Class                        | Pilot Devices                                                                                                                                                                                                                                                                                                              |

Technical UL/CSA

|                     |                |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA              | 2x 18...14 AWG |

Environmental

|                      |                                                           |
|----------------------|-----------------------------------------------------------|
| Degree of Protection | Front IP66<br>Front IP67<br>Front IP69K<br>Terminals IP20 |
|----------------------|-----------------------------------------------------------|

Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                           | 2CMT2022-006479                                                        |
| RoHS Information                            | 2CMT2022-006498                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006523                                                        |
| WEEE B2C / B2B                              | Business To Business                                                   |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm)             |

## Certificates and Declarations

|                                  |                     |
|----------------------------------|---------------------|
| CB Certificate                   | CQC_CN_CN50749      |
| CQC Certificate                  | CQC2003010305054693 |
| cURus Certificate                | UL_E496500-20171020 |
| Declaration of Conformity - CCC  | 2020980305001187    |
| Declaration of Conformity - CE   | 2CMT2015-005451     |
| Declaration of Conformity - UKCA | 2CMT2020-006121     |
| DNV GL Certificate               | 9AKK107046A3749     |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | bag 10 piece  |
| Package Level 1 Width          | 0.235 m       |
| Package Level 1 Depth / Length | 0.125 m       |
| Package Level 1 Height         | 0.035 m       |
| Package Level 1 Gross Weight   | 0.18 kg       |
| Package Level 1 EAN            | 7320500204160 |

## Classifications

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Object Classification Code         | P                                   |
| ETIM 6                             | EC000272 - Indicator light complete |
| ETIM 7                             | EC000272 - Indicator light complete |
| ETIM 8                             | EC000272 - Indicator light complete |
| eClass                             | V11.0 : 27371223                    |
| UNSPSC                             | 39121534                            |
| IDEA Granular Category Code (IGCC) | 4766 >> Indicator or pilot lights   |
| E-Number (Finland)                 | 2314759                             |
| E-Number (Norway)                  | 4372568                             |
| E-Number (Sweden)                  | 3711210                             |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CL Compact Pilot Lights

