OTM2000E3CM230C 1/4



PRODUCT-DETAILS

OTM2000E3CM230C OTM2000E3CM230C MOTORIZED C/O SWITCH



General Information	
Extended Product Type	OTM2000E3CM230C
Product ID	1SCA112709R1001
EAN	6417019454054
Catalog Description	OTM2000E3CM230C MOTORIZED C/O SWITCH
Long Description	OTM2000E3CM230C MOTORIZED C/O SWITCH, Direct mounted handle, Open transition

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	1SCC303061M0201
Environmental Information	1SCC303036D0202
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

OTM2000E3CM230C 2/4

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204
End of Life Instructions	1SCC303061M0201

Dimensions	
Product Net Width	645 mm
Product Net Height	377 mm
Product Net Depth / Length	335 mm
Product Net Weight	645 lb 78 kg

Technical	
Rated Operational Current AC-21B (I _e)	(380 415 V) 2000 A (500 V) 2000 A
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 2000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 55 kiloampere rms
Motor Operational Voltage	220 240 V AC
Power Loss	55 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

OTM2000E3CM230C 3/4

Environmental	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental	1SCC303036D0202
Information	

Certificates and Declarations	
Declaration of	1SCC303028D0201
Conformity - CE	
REACH Declaration	1SCC011021D0201

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	580 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	500 mm
Package Level 1 Gross Weight	78 kg
Package Level 1 EAN	6417019454054

Classifications	
Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1: 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3641796

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switches \rightarrow Change-over\ and\ Transfer\ Switches \rightarrow Motorized\ Change-over\ Switches$

OTM2000E3CM230C 4/4

