



PRODUCT-DETAILS

# LD38-4

## LD38-4 Additional Terminal Block



General Information	
Extended Product Type	LD38-4
Product ID	1SBN072308R1000
EAN	3471523130838
Catalog Description	LD38-4 Additional Terminal Block
Long Description	LD38-4 is an additional terminal block designed to increase the connecting capacity of 3-pole AF(C)(S)26 ... 38 contactors on which it is fitted and for preparation of the wiring before final connection to the contactor. LD38-4 blocks is 3-pole terminal block with tunnel terminals.

Ordering	
Minimum Order Quantity	2 piece
Customs Tariff Number	85369010

Popular Downloads	
CAD Dimensional Drawing	2CDC001079B0201

<b>Dimensions</b>	
Product Net Width	44.8 mm
Product Net Depth / Length	50 mm
Product Net Height	40.5 mm
Product Net Weight	0.07 kg

<b>Technical</b>	
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 2.5 ... 16 mm <sup>2</sup> Flexible with Ferrule 1/1x 2.5 ...10/...16 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 2.5 ... 16 mm <sup>2</sup> Flexible with Insulated Ferrule 1/1x 2.5 ...10/...16 mm <sup>2</sup> Rigid Solid 1/2x 2.5 ... 4 mm <sup>2</sup> Rigid Stranded 1/1x 6 ...16/ ... 25 mm <sup>2</sup>
Wire Stripping Length	Main Circuit 14 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M5 with 2 x (7 width x 5.8/9.2 depth) double connector
Terminal Type	Screw Terminals
Suitable For	AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC26 AFC30 AFC38

<b>Technical UL/CSA</b>	
Connecting Capacity Main Circuit UL/CSA	1x 8-4 AWG 2x 8-6 AWG
Tightening Torque UL/CSA	Main Circuit 22 in-lb

<b>Material Compliance</b>	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

<b>Certificates and Declarations</b>
--------------------------------------

Declaration of Conformity - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
UL Certificate	UL-US-2150887-5 UL-CA-2142658-5

Container Information

Package Level 1 Units	bag 2 piece
Package Level 1 Width	90 mm
Package Level 1 Depth / Length	160 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	3471523130838

Classifications

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.1 : 27371392
UNSPSC	39121410
IDEA Granular Category Code (IGCC)	4547 >> Terminal blocks
E-Number (Sweden)	3210256

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

