




PRODUCT-DETAILS

LF38-4

LF38-4 Connecting Strip



| General Information | |
|-----------------------|---|
| Extended Product Type | LF38-4 |
| Product ID | 1SBN072305R1000 |
| EAN | 3471523130906 |
| Catalog Description | LF38-4 Connecting Strip |
| Long Description | LF38-4 is an insulated connecting strip used on 3 or 4-pole AF(C)(S)09..16 contactors, equipped with a main terminal screw used to connect 3 poles in parallel and thus increase the AC load passing through the flow path made up of the parallel-connected poles. The relevant cable cross-sectional area may limit the maximum permissible current: consult technical data information on catalogue. |

| Ordering | |
|------------------------|----------|
| Minimum Order Quantity | 2 piece |
| Customs Tariff Number | 85369010 |

| Popular Downloads | |
|-------------------|-----------------|
| CAD Dimensional | 2CDC001079B0201 |

Drawing

| Dimensions | |
|----------------------------|---------|
| Product Net Width | 32.6 mm |
| Product Net Depth / Length | 52 mm |
| Product Net Height | 46.2 mm |
| Product Net Weight | 0.04 kg |

| Technical | |
|----------------------------------|---|
| Standards | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1 |
| Rated Frequency (f) | Main Circuit 50 / 60 Hz |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1x 6 ... 35 mm² Flexible with Insulated Ferrule 1x 6 ... 35 mm² Rigid 1x 6 ... 50 mm² |
| Wire Stripping Length | Main Circuit 18 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Terminal Type | Screw Terminals |
| Suitable For | AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC26 AFC30 AFC38 |

| Technical UL/CSA | |
|---|-----------------------|
| Connecting Capacity Main Circuit UL/CSA | 1x 8-1 AWG |
| Tightening Torque UL/CSA | Main Circuit 35 in-lb |

| Material Compliance | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2021-006202 |
| RoHS Information | 2CMT2021-006277 |
| RoHS Status | Following EU Directive 2011/65/EU |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

| Certificates and Declarations | |
|----------------------------------|-----------------------------|
| Declaration of Conformity - CE | 1SBD250021U1000 |
| Declaration of Conformity - UKCA | 1SBD250043U1000 |
| GOST Certificate | GOST_POCCFR.ME77.B07175.pdf |
| UL Certificate | UL-US-2150887-5 |

| | |
|-----------------|-----------------|
| | UL-CA-2142658-5 |
| UL Listing Card | UL_E312527 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | bag 2 piece |
| Package Level 1 Width | 90 mm |
| Package Level 1 Depth / Length | 160 mm |
| Package Level 1 Height | 38 mm |
| Package Level 1 Gross Weight | 0.08 kg |
| Package Level 1 EAN | 3471523130906 |

Classifications

| | |
|------------------------------------|--|
| ETIM 4 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 6 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 7 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 8 | EC002498 - Accessories/spare parts for low-voltage switch technology |
| eClass | V11.1 : 27371392 |
| UNSPSC | 39121407 |
| IDEA Granular Category Code (IGCC) | 4538 >> Terminal strips |
| E-Number (Sweden) | 3210253 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

