



PRODUCT-DETAILS

LFH-SP25/25M

LOW FIR.HAZ.LIQ.PROOF NC25 25MT BLK



| General Information   |                                                                                                                                                                                                                                                                   |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | LFH-SP25/25M                                                                                                                                                                                                                                                      |
| Product ID            | 7TCA296130R0011                                                                                                                                                                                                                                                   |
| EAN                   | 5020963000409                                                                                                                                                                                                                                                     |
| Catalog Description   | LOW FIR.HAZ.LIQ.PROOF NC25 25MT BLK                                                                                                                                                                                                                               |
| Long Description      | Low Fire Hazard, Medium Flexibility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black |

| Additional Information |                                                                   |
|------------------------|-------------------------------------------------------------------|
| Application            | Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern |
| Product Type           | Medium Flexibility Conduit                                        |

| Ordering |               |
|----------|---------------|
| EAN      | 5020963000409 |
| UPC      | 786210277806  |

|                            |      |
|----------------------------|------|
| <b>Dimensions</b>          |      |
| Product Net Depth / Length | 25 m |

|                     |                                                   |
|---------------------|---------------------------------------------------|
| <b>Technical</b>    |                                                   |
| Number of Batteries | 0                                                 |
| Color               | Black                                             |
| Material            | Galvanized Steel Core with Low Fire Hazard Jacket |

|                      |                           |
|----------------------|---------------------------|
| <b>Environmental</b> |                           |
| WEEE Category        | Product Not in WEEE Scope |

|                                |                 |
|--------------------------------|-----------------|
| <b>Container Information</b>   |                 |
| Package Level 1 Units          | 1 piece         |
| Package Level 1 Height         | 7 in<br>178 mm  |
| Package Level 1 Depth / Length | 16 in<br>406 mm |
| Package Level 1 Width          | 16 in<br>406 mm |

|                                      |                 |
|--------------------------------------|-----------------|
| <b>Certificates and Declarations</b> |                 |
| Data Sheet, Technical Information    | LFH-SP25/25M    |
| Instructions and Manuals             | LFH-SP25/25M    |
| Declaration of Conformity - CE       | 9AKK107492A9618 |
| RoHS Information                     | 9AKK107992A8994 |
| RoHS Date                            | 9AKK107992A8994 |
| REACH Declaration                    | 9AKK107992A8994 |

|                        |                                     |
|------------------------|-------------------------------------|
| <b>Classifications</b> |                                     |
| ETIM 8                 | EC001179 - Protective metallic hose |
| UNSPSC                 | 39131706                            |

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

