



PRODUCT-DETAILS

LFH-SP50/10M
LOW FIR.HAZ.LIQ.PROOF NC50 10MT BLK



General Information	
Extended Product Type	LFH-SP50/10M
Product ID	7TCA296130R0019
EAN	5020963048906
Catalog Description	LOW FIR.HAZ.LIQ.PROOF NC50 10MT BLK
Long Description	Low Fire Hazard, Medium Flexibility Conduit, 1-1/2 Inch, Nominal Conduit Size 50mm, Outside Diameter 55.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Additional Information	
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Medium Flexibility Conduit

Ordering	
EAN	5020963048906
UPC	786210277837

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	9.37 in 238 mm
Package Level 1 Depth / Length	19.25 in 489 mm
Package Level 1 Width	19.25 in 489 mm

Certificates and Declarations	
Data Sheet, Technical Information	LFH-SP50/10M
Instructions and Manuals	LFH-SP50/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

