



PRODUCT-DETAILS

LFH-SP63/25M  
LOW FIR.HAZ.LIQ.PROOF NC63 25MT BLK



General Information	
Extended Product Type	LFH-SP63/25M
Product ID	7TCA296130R0022
EAN	5020963019401
Catalog Description	LOW FIR.HAZ.LIQ.PROOF NC63 25MT BLK
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 63mm, Outside Diameter 64.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Additional Information	
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Medium Flexibility Conduit

Ordering	
EAN	5020963019401
UPC	786210248608

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	LFH-SP63/25M
Instructions and Manuals	LFH-SP63/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

