



PRODUCT-DETAILS

LFH-SPL20/10M
LOW FIR.HAZ.LIQ.TIGHT NC20 10MT BLK



Product image
not available

General Information	
Extended Product Type	LFH-SPL20/10M
Product ID	7TCA296030R0403
EAN	5020963800702
Catalog Description	LOW FIR.HAZ.LIQ.TIGHT NC20 10MT BLK
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 80mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Additional Information	
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Low Fire Hazard Conduit

Ordering	
EAN	5020963800702
UPC	786210289694

Dimensions	
Product Net Depth / Length	10 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Jacket

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 1 Width	16 in 406 mm

Certificates and Declarations	
Data Sheet, Technical Information	LFH-SPL20/10M
Instructions and Manuals	LFH-SPL20/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available