



PRODUCT-DETAILS

LFH-SPL63/10M**LOW FIR.HAZ.LIQ.TIGHT NC63 10MT BLK**Product image
not available**General Information**

Extended Product Type	LFH-SPL63/10M
Product ID	7TCA296030R0411
EAN	5020963800788
Catalog Description	LOW FIR.HAZ.LIQ.TIGHT NC63 10MT BLK
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, 2 Inch, Nominal Conduit Size 63mm, Outside Diameter 64.5mm, Inside Diameter 57.5mm, Static Bend Radius 345mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Low Fire Hazard Conduit

Ordering

EAN	5020963800788
UPC	786210289601

Dimensions

Product Net Depth / Length	10 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Jacket

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 1 Width	26.77 in 680 mm

Certificates and Declarations

Data Sheet, Technical Information	LFH-SPL63/10M
Instructions and Manuals	LFH-SPL63/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications

ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available