



PRODUCT-DETAILS

LFH-SPSS20/25M
SS BRDD.LOW FIRE HAZ. NC20 25MT BLK



General Information	
Extended Product Type	LFH-SPSS20/25M
Product ID	7TCA296100R0020
EAN	5020963050435
Catalog Description	SS BRDD.LOW FIRE HAZ. NC20 25MT BLK
Long Description	Low Fire Hazard, Medium Flexibility Conduit with Stainless Steel Overbraid, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 80mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Additional Information	
Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Medium Flexibility Conduit

Ordering	
EAN	5020963050435
UPC	786210248530

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with LFH Jacket and Stainless Steel Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	7 in 178 mm
Package Level 1 Depth / Length	13 in 330 mm
Package Level 1 Width	13 in 330 mm

Certificates and Declarations	
Data Sheet, Technical Information	7TK001224
Instructions and Manuals	LFH-SPSS20/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

