



PRODUCT-DETAILS

LS45P42B11

LS45P42B11 Limit Switch



General Information

Extended Product Type	LS45P42B11
Product ID	1SBV012442R1211
EAN	3471522611758
Catalog Description	LS45P42B11 Limit Switch
Long Description	LS45P42B11 is a 40 mm wide, standard reinforced Limit Switch made of fiber-glass reinforced UL-V0 material, with 4 mounting holes at the top and bottom, 1 1/2" NPT cable entry on the bottom, steel roller lever (Ø22 mm) actuator and 1 N.O + 1 N.C snap action (Zb type) contacts

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC141160C0201
Instructions and Manuals	1SBC141160C0201

Dimensions

Product Net Width	41 mm
Product Net Height	130 mm
Product Net Depth / Length	59 mm
<u>Product Net Weight</u>	<u>0.178 kg</u>

Technical

Action Type of the Contact Element (acc. to IEC 60947-5-1)	Snap action contacts
Actuation Speed	acc. to IEC 60947-5-1 Max. 1.5 m/s
Actuation Torque	acc. to IEC 60947-5-1 Min. 0.15 N·m
Actuator Type	Ø 22 mm stainless steel roller lever
Angular Head Adjustment	adjustable head every 90°
Angular Lever Adjustment	9° in 9°
B10d Value	Operations 50 Millions
Climatic Withstand	according to IEC 68-2-3 and salty mist according to IEC 68-2-11
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-5-1, Θ = 40 °C 10 A
Connecting Capacity	Bar AWG 20 ... AWG 14 mm ² Bar 0.5 ... 2.5 mm ²
Consistency (Measured over 1 Million Operations)	0.1 mm
Contact Element Form (acc. to IEC 60947-5-1)	Zb
Connecting Terminals (delivered in open position)	M3.5 (+,-) pozidriv 2 screw with cable clamp
Degree of Protection	acc. to IEC 60529 IP65
Electrical Shock Protection acc. to IEC 536	Double insulation - Class II
Flammability According to UL94	V-0
Housing Material	Plastic
Maximum Electrical Switching Frequency	3600 cycles per hour (AC-15) 3600 cycles per hour (DC-13) 3600 cycles per hour
Maximum Mounted Auxiliary Contacts	1 NO, 1 NC
Mechanical Durability	0 cycle
Mounting Type	40 mm (EN 50041)
Mounting by Screws (not supplied)	2 or 4 x M5 screws
Movement to be Detected	30° Cam Translation Movement
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number and Type of Bottom Cable Glands	1/2 NPT cable gland
Operating Head Shape	A shape acc. EN 50041
Pilot Duty UL/CSA	A600 Q600
Positive Opening Operation Torque (Direct Opening Action)	Minimum Torque acc. to IEC 60947-5-1 0.32 N·m
Positive Opening Operation of NC Contact (s)	Yes
Rated Impulse Withstand	6 kV

Voltage (U_{imp})

Rated Operational Current AC-15 (I _e)	(230 V AC) 3.1 A (400 V) NC 4 (24 V) 10 A (130 V) 5.5 A (240 V) 3 A
--	---

Rated Frequency (f)

Supply Circuit 50 / 60 Hz

Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 500 V acc. to UL/CSA 600 V
---	--

Rated Operational Current
DC-13 (I_e)(24 V) 6 A
(110 V) 0.6 A
(125 V) 0.55 A
(250 V) 0.4 AResistance Between
Contacts

25 E45

Short-Circuit Protective
Devices

gG Type Fuses 10 A

Terminal Marking

according to EN 50013

Environmental

Ambient Air Temperature

Operation -25 ... +70 °C
Storage -30 ... +80 °CResistance to Shock acc.
to IEC 60068-2-27Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s²

Resistance to Vibrations

No Change in Position of Contacts Greater than 100 µs: 25g 10 ... 500 Hz

Material Compliance

Conflict Minerals

9AKK108467A5658

Reporting Template
(CMRT)

REACH Declaration

1SBD251097E1000

RoHS Information

1SBD251097E1000

RoHS Status

Following EU Directive 2011/65/EU

WEEE B2C / B2B

Business To Business

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CQC Certificate

CQC2004010305127663

cUL Certificate

9AKK107991A7379

Declaration of Conformity
- CCC

2020980305001785

Declaration of Conformity
- CE

1SBD250883U1000

Declaration of Conformity
- UKCA

1SBD250886U1000

Container Information

Package Level 1 Units

box 1 piece

Package Level 1 Width

45 mm

Package Level 1 Depth /
Length

70 mm

Package Level 1 Height

140 mm

Package Level 1 Gross
Weight

0.199 kg

Package Level 1 EAN

3471522611758

Classifications

Object Classification Code	B
ETIM 6	EC000030 - End switch
ETIM 7	EC000030 - End switch
ETIM 8	EC000030 - End switch
eClass	V11.0 : 27272601
UNSPSC	39121500

Categories

Low Voltage Products and Systems → Control Products → Sensors → Limit Switches

