



PRODUCT-DETAILS

E211X-25-10

ON-OFF Switch, 25 A, acc. to EN 250/400 V AC, 1NO, El. Color: Grey, 1LED, Yellow, MW: 0.5



General Information	
Extended Product Type	E211X-25-10
Product ID	2CCA703101R0001
EAN	7612270938902
Catalog Description	ON-OFF Switch, 25 A, acc. to EN 250/400 V AC, 1NO, El. Color: Grey, 1LED, Yellow, MW: 0.5
Long Description	On-Off switches with switch position indication, according DIN EN 60669-1, VDE 0632 Part 1, Rated currents: 16/25 A, 250 VACPDC, Contacts: 1 NO/2 NO/3 NO, Module width: 0,5/1

Technical	
Standards	EN60669-1 EN60669-2-4 IEC/EN60947-3 IEC60068-2-2 IEC60068-2-1 IEC60068-2-30 VDE0632-1 VDE0632-2-4 UL508

Rated Voltage (U _r)	Minimum 250 V
Rated Operational Voltage	acc. to EN 250/400 V AC acc. to UL 508 240 V AC
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Auxiliary Voltage AC/DC	LED Indicator 115...250 V AC
Input Voltage Type	AC
Rated Current (I _n)	25 A
Rated Service Short-Circuit Breaking Capacity (I _{cs})	3 kA
Rated Frequency (f)	50/60 Hz
Minimum Switching Capacity	24 V AC 25 mA
Power Watt	0.18 W
Contact Position Indication	ON / OFF
Number of Contacts NO	1
Number of Main Contacts NC	0
Number of Main Contacts NO	1
Number of Auxiliary Contacts CO (SPDT)	0
Number of Poles	1
Number of LEDs	1
Tightening Torque	1.2-1.5 N·m
Utilization Category	Switching of mixed resistive and inductive loads, including moderate overloads - frequent actuation (AC-22A) Switching of mixed resistive and inductive loads, including moderate overloads (i.e. shunt motors) - frequent actuation (DC-22A)
Lamp Type	LED
Switch Type	Double Interrupting Contacts
Material of Conductor	Copper
Remarks	Sealable in the On and Off positions
Color	Yellow
Cover Color	Grey
Control Element Color	Grey
Lamp Color	Yellow
Connecting Capacity	Solid 1x1...6 mm ² Solid 2x2.5 mm ² Flexible 1x0.75...2x2.5 mm ²
Rated Operational Current AC-22A (I _e)	(400 V) 25 A
Rated Operational Current DC-22A (I _e)	(50 V DC) 25 A (200 V DC) 2 A

Material Compliance

RoHS Information	2CCC441013D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	2CCC005047D0201
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -25...+55 °C Storage -40...+70 °C
Degree of Protection	IP20
Environmental Information	2CCC441003C0201

Technical UL/CSA	
Short-Circuit Current Rating (SCCR)	3 kA

Dimensions	
Width in Number of Modular Spacings	0.5
Product Net Width	9 mm
Product Net Height	85 mm
Product Net Depth / Length	68 mm
Product Net Weight	40 g
Built-In Depth (t ₂)	68 mm

Ordering	
Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	43 g
E-Number (Finland)	3602415
E-Number (Switzerland)	437260438

Certificates and Declarations	
CB Certificate	9AKK108466A3838
CCC Certificate	9AKK108466A3918
Declaration of Conformity - CE	2CCC441013D0201
Declaration of Conformity - UKCA	9AKK108467A6122
VDE Certificate	9AKK108466A3836

Installation	
Instructions and Manuals	No document needed

Popular Downloads	
Data Sheet, Technical Information	2CCC441003C0101

Classifications		
ETIM 8	EC001545 - Main switch for distribution board	
ETIM 9	EC001545 - Main switch for distribution board	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
CN8	85365053	
eClass	V11.0 : 27142301	
Object Classification Code	S	

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights → Switches, Pushbuttons and Indicator Lights, E210

