



PRODUCT-DETAILS

ISL-A 24-48

ISL-A 24-48 Insulation monitor



General Information	
Extended Product Type	ISL-A 24-48
Product ID	2CSM111000R1500
EAN	8012542942504
Catalog Description	ISL-A 24-48 Insulation monitor
Long Description	ISL-A 24-48 is an insulation monitoring device for dc circuits
Technical	
Rated Operational Voltage	24 ... 48 V AC/DC
Rated Control Supply Voltage (U _s)	(50 Hz) 24...28 V (50 Hz) 24...28 V (60 Hz) 24...28 V (60 Hz) 24...28 V (DC) 24...28 V (DC) 24...28 V
Power Loss	at Rated Operating Conditions per Pole 4 W
Model Number	Basic device
Delay Time (T)	Release 0...0 second [unit of time]

Options Provided

AC/DC network

Material Compliance

RoHS Information	9AKK106713A5707
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20231022
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Environmental Information	See RoHS Information
---------------------------	----------------------

Dimensions

Product Net Width	85 mm
Product Net Height	0.085 m
Product Net Depth / Length	58 mm
Product Net Weight	0.090 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.3 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5707
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK108469A0613 9AKK108469A0975
--------------------------	------------------------------------

Popular Downloads

Data Sheet, Technical Information	9AKK108469A0611
-----------------------------------	-----------------

Classifications

ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

CN8	90303100
eClass	V11.0 : 27371819
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Industrial Insulation Monitoring Devices

