



PRODUCT-DETAILS

E 9F8 AM8

E 9F8 AM8 Fuse link



General Information	
Extended Product Type	E 9F8 AM8
Product ID	2CSM256383R1801
EAN	8012542563839
Catalog Description	E 9F8 AM8 Fuse link
Long Description	E 9F8 AM8 is a 8,5x31,5 mm cylindrical fuse for motor protection

Technical	
Standards	IEC 60269-2
Rated Voltage (U _r)	400 V
Rated Current (I _n)	8 A
Maximum Breaking Capacity	20 kA
Power Loss	at Rated Operating Conditions per Pole 0.47 W
Fuse Type	aM
Release Type	aM: Used in short-circuit protection of motor circuits
Construction Material	Ceramic
Fuse Size	8x32

Contact Material

copper silver plated (Cu/Ag)

Material Compliance

RoHS Information	9AKK106713A5625
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	27/01/2014
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Environmental Information	See RoHS Information
---------------------------	----------------------

Dimensions

Product Net Width	0.008 m
Product Net Height	0.031 m
Product Net Depth / Length	0.009 m
Product Net Weight	0.004 kg
Dimension Diagram	9AKK108466A8531

Ordering

Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	0.045 kg

Certificates and Declarations

Cut-off Current Characteristic	9AKK108466A9058
Declaration of Conformity - CE	9AKK106713A5625
I ² t Characteristic	9AKK108466A9079

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	9AKK107991A8329
Cut-off Current Characteristic	9AKK108466A9058
I ² t Characteristic	9AKK108466A9079

Classifications

ETIM 8	EC002704 - Cylindrical fuse
ETIM 9	EC002704 - Cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361010
eClass	V11.0 : 27142002
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

