



PRODUCT-DETAILS

E 9F14 GG32

E 9F14 GG32 Fuse link



| General Information   |                                                                    |
|-----------------------|--------------------------------------------------------------------|
| Extended Product Type | E 9F14 GG32                                                        |
| Product ID            | 2CSM258693R1801                                                    |
| EAN                   | 8012542586937                                                      |
| Catalog Description   | E 9F14 GG32 Fuse link                                              |
| Long Description      | E 9F14 GG32 is a 14x51 mm cylindrical fuse for circuits protection |

| Technical                 |                                                                                                |
|---------------------------|------------------------------------------------------------------------------------------------|
| Standards                 | IEC 60269-2                                                                                    |
| Rated Voltage ( $U_r$ )   | 500 V                                                                                          |
| Rated Current ( $I_n$ )   | 32 A                                                                                           |
| Maximum Breaking Capacity | 120 kA                                                                                         |
| Power Loss                | at Rated Operating Conditions per Pole 3.6 W                                                   |
| Fuse Type                 | gG                                                                                             |
| Release Type              | gG: Used in general protection of cables and lines in installation and industrial applications |
| Construction Material     | Ceramic                                                                                        |

|                  |                              |
|------------------|------------------------------|
| Fuse Size        | 14x51                        |
| Contact Material | copper silver plated (Cu/Ag) |

### Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| RoHS Information                            | 9AKK106713A5625                                                        |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date                                   | 27/01/2014                                                             |
| REACH Declaration                           | 9AKK108467A9482                                                        |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363                                                        |

### Environmental

|                           |                      |
|---------------------------|----------------------|
| Environmental Information | See RoHS Information |
|---------------------------|----------------------|

### Dimensions

|                            |                 |
|----------------------------|-----------------|
| Product Net Width          | 0.001 m         |
| Product Net Height         | 0.051 m         |
| Product Net Depth / Length | 0.001 m         |
| Product Net Weight         | 0.006 kg        |
| Dimension Diagram          | 9AKK108466A8533 |

### Ordering

|                              |              |
|------------------------------|--------------|
| Package Level 1 Units        | box 10 piece |
| Package Level 1 Gross Weight | 0.19 kg      |

### Certificates and Declarations

|                                 |                 |
|---------------------------------|-----------------|
| Cut-off Current Characteristic  | 9AKK108466A9072 |
| Declaration of Conformity - CE  | 9AKK106713A5625 |
| I <sup>2</sup> t Characteristic | 9AKK108467A0128 |

### Installation

|                          |                    |
|--------------------------|--------------------|
| Instructions and Manuals | No document needed |
|--------------------------|--------------------|

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |
| Cut-off Current Characteristic    | 9AKK108466A9072 |

|                                      |                 |
|--------------------------------------|-----------------|
| I²t Characteristic                   | 9AKK108467A0128 |
| Time-Current<br>Characteristic Curve | 9AKK108467A0149 |

Classifications

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| ETIM 8                        | EC002704 - Cylindrical fuse                                |
| ETIM 9                        | EC002704 - Cylindrical fuse                                |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                | Business To Consumer                                       |
| CN8                           | 85361050                                                   |
| eClass                        | V11.0 : 27142002                                           |
| Object Classification<br>Code | F                                                          |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

