



PRODUCT-DETAILS

E 9F8 AM4
E 9F8 AM4 Fuse link



General Information	
Extended Product Type	E 9F8 AM4
Product ID	2CSM258743R1801
EAN	8012542587439
Catalog Description	E 9F8 AM4 Fuse link
Long Description	E 9F8 AM4 is a 8.5x31.5 mm cylindrical fuse for motor protection

Technical	
Standards	IEC 60269-2
Rated Voltage (U_r)	400 V
Rated Current (I_n)	4 A
Maximum Breaking Capacity	20 kA
Power Loss	at Rated Operating Conditions per Pole 0.26 W
Fuse Type	aM
Release Type	aM: Used in short-circuit protection of motor circuits
Construction Material	Ceramic
Fuse Size	8x32
Contact Material	copper silver plated (Cu/Ag)

Material Compliance		
RoHS Information		9AKK106713A5625
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
RoHS Date		27/01/2014
REACH Declaration		9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)		9AKK108468A3363

Environmental		
Environmental Information		See RoHS Information

Dimensions		
Product Net Width		0.008 m
Product Net Height		0.031 m
Product Net Depth / Length		0.009 m
Product Net Weight		0.004 kg
Dimension Diagram		9AKK108466A8531

Ordering		
Package Level 1 Units		box 10 piece
Package Level 1 Gross Weight		0.045 kg

Certificates and Declarations		
Cut-off Current Characteristic		9AKK108466A9058
Declaration of Conformity - CE		9AKK106713A5625
I ² t Characteristic		9AKK108466A9079

Installation		
Instructions and Manuals		No document needed

Popular Downloads		
Data Sheet, Technical Information		9AKK107991A8329
Cut-off Current Characteristic		9AKK108466A9058
I ² t Characteristic		9AKK108466A9079
Time-Current Characteristic Curve		9AKK108467A0137

Classifications		
ETIM 8		EC002704 - Cylindrical fuse

ETIM 9	EC002704 - Cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85361010
eClass	V11.0 : 27142002
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

