



PRODUCT-DETAILS

ISL-A 230

ISL-A 230 Insulation monitor



General Information	
Extended Product Type	ISL-A 230
Product ID	2CSM333000R1500
EAN	8012542942702
Catalog Description	ISL-A 230 Insulation monitor
Long Description	ISL-A 230 is an insulation monitoring device for dc circuits

Technical	
Rated Operational Voltage	220 V DC
Rated Control Supply Voltage (U _s)	(DC) 220...220 V
Power Loss	at Rated Operating Conditions per Pole 4 W
Model Number	Basic device
Delay Time (T)	Release 0...0 second [unit of time]
Options Provided	DC network

Material Compliance	
RoHS Information	9AKK106713A5707
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20231022
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Environmental Information	See RoHS Information

Dimensions	
Product Net Width	90 mm
Product Net Height	0.105 m
Product Net Depth / Length	58 mm
Product Net Weight	0.250 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.5 kg

Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5707

Installation	
Instructions and Manuals	9AKK108469A0617 9AKK108469A0987

Popular Downloads	
Data Sheet, Technical Information	9AKK108469A0611

Classifications	
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
ETIM 9	EC001449 - Device for monitoring of safety-related circuits
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	90303100
eClass	V11.0 : 27371819
Object Classification	F

Code

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Industrial Insulation Monitoring Devices

