



PRODUCT-DETAILS

SD202/40

SD202/40 Switch Disconnecter



General Information	
Extended Product Type	SD202/40
Product ID	2CDD282101R0040
EAN	4016779904155
Catalog Description	SD202/40 Switch Disconnecter
Long Description	SD202/40 - Switch Disconnecter - 2P, 40A

Technical	
Standards	IEC/EN 60947-3
Rated Voltage (U _r)	440 V 12 V Minimum
Rated Operational Voltage	440 V AC 125 V DC
Operational Voltage	Maximum 462 V AC Maximum 131 V DC Minimum 12 V AC
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV

Input Voltage Type	AC/DC
Rated Current (I _n)	40 A
Rated Conditional Short-Circuit Current (I _{nc})	25 kA
Rated Frequency (f)	50 / 60 Hz DC
Power Loss	at Rated Operating Conditions per Pole 2.27 W
Contact Position Indication	ON / OFF
Electrical Endurance	10000 AC cycle
Mechanical Endurance	20000 cycle
Number of Contacts CO	0
Number of Contacts NC	0
Number of Contacts NO	2
Number of Poles	2
Overvoltage Category	III
Tightening Torque	2.8 N·m
Utilization Category	Switching of motor loads or other highly inductive loads - frequent actuation (AC-23A) Switching of resistive loads, including moderate overloads - frequent actuation (DC-21A)
Actuator Type	Toggle
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Switch Type	Off
Actuator Marking	I / O
Actuator Material	Insulation Group II, Red, Sealable
Housing Material	Insulation Group I, RAL 7035
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Cover Color	Grey
Connecting Capacity	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Terminal Type	Screw Terminals

Material Compliance	
RoHS Information	2CDK440034D2703
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20210528
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Degree of Protection	IP20 Enclosure with Cover IP40

Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	2CDK400618D0201

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	88 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.17 kg
Built-In Depth (t ₂)	69 mm

Ordering

Package Level 1 Units	5 piece
Package Level 1 Gross Weight	0.9 kg
E-Number (Finland)	3601633

Certificates and Declarations

Certification Agency	IEC EN
Declaration of Conformity - CE	2CDK440034D2703

Installation

Instructions and Manuals	2CDC441015D0201
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CDC441015D0201
-----------------------------------	-----------------

Classifications

ETIM 8	EC001545 - Main switch for distribution board
ETIM 9	EC001545 - Main switch for distribution board
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 90 95
eClass	V11.0 : 27142301

Accessories					
Identifier	Description	Type	Quantity	Unit Of Measure	
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece	
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece	
2CDS200970R0001	S2C-H01 Auxiliary Contact	S2C-H01	1	piece	
2CDS200970R0002	S2C-H10 Auxiliary Contact	S2C-H10	1	piece	
2CDS200936R0001	S2C-H11L Auxiliary Contact	S2C-H11L	1	piece	
2CDS200936R0002	S2C-H20L Auxiliary Contact	S2C-H20L	1	piece	
2CDS200936R0003	S2C-H02L Auxiliary Contact	S2C-H02L	1	piece	
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece	
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece	
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece	
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece	
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece	
2CSS200911R0001	S2C-UA 12 DC Undervoltage Release	S2C-UA 12 DC	1	piece	
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece	
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece	
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece	
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece	
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece	
2CSS200911R0007	S2C-UA 24 DC Undervoltage Release	S2C-UA 24 DC	1	piece	
2CSS200911R0008	S2C-UA 48 DC Undervoltage Release	S2C-UA 48 DC	1	piece	
2CSS200911R0009	S2C-UA 110 DC Undervoltage Release	S2C-UA 110 DC	1	piece	
2CSS200911R0010	S2C-UA 230 DC Undervoltage Release	S2C-UA 230 DC	1	piece	
2CSS201997R0013	S2C-CM1 Motor Operating Device	S2C-CM1	1	piece	
2CSS203997R0013	S2C-CM2/3 Motor Operating Device	S2C-CM2/3	1	piece	
2CSS204997R0013	S2C-CM4 Motor Operating Device	S2C-CM4	1	piece	
GHS2001901R0003	S2C-DH Mechanical Accessories	S2C-DH	1	piece	
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece	
2CSS200999R0001	S2C-EST Plug-in base	S2C-EST	1	piece	
2CDS200918R0001	S2C-NT Hand Operated Neutral	S2C-NT	1	piece	
2CCA880100R0001	CMS-100PS Sensor	CMS-100PS	1	piece	
2CCA880101R0001	CMS-101PS Sensor	CMS-101PS	1	piece	
2CCA880102R0001	CMS-102PS Sensor	CMS-102PS	1	piece	

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Switch Disconnectors

Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)



360°