



PRODUCT-DETAILS

MLP125-C-A
SHRINK-KON 25X1,2M TRANSP.



General Information	
Extended Product Type	MLP125-C-A
Product ID	7TCA017300R0430
EAN	5414363104896
Catalog Description	SHRINK-KON 25X1,2M TRANSP.
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 1/8 Inch/3.2mm Expanded Diameter, Transparent, 25 X 1.22M Lengths

Ordering	
EAN	5414363104896
UPC	786210597980
Country of Origin	Germany (DE)
Selling Unit of Measure	each

Dimensions	
Product Net Depth / Length	4 ft 1.22 m

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	4.1 in 104 mm
Package Level 1 Height	4.2 in 107 mm
Package Level 1 Depth / Length	49.3 in 1252 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Transparent
Effective Date	19980621
Flammability Hazard Rating	Flame Retardant
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	Plastic conduit
Product Type	Thin-Wall Heat Shrinkable Tubing
RoHS Date	9AKK108466A3883
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin

Certificates and Declarations

Data Sheet, Technical Information	MLP125-C-A
-----------------------------------	------------

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
ETIM 8	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

