



PRODUCT-DETAILS

MLP375-0-BG
SHRINK-KON 150M BLACK



General Information	
Extended Product Type	MLP375-0-BG
Product ID	7TCA017300R0453
EAN	5414363105213
Catalog Description	SHRINK-KON 150M BLACK
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 3/8 Inch/9.5mm Expanded Diameter, Black, 150M, CrossLinked Polyolefin, Item is Silicone, Cadmium and Lead Free

Ordering	
EAN	5414363105213
UPC	786210495989
Country of Origin	Germany (DE)
Selling Unit of Measure	roll

Dimensions	
Product Net Depth /	492.1 ft

Length	150 m
--------	-------

Container Information

Package Level 1 Units	1 reel
Package Level 1 Width	15.4 in 391 mm
Package Level 1 Height	10.3 in 262 mm
Package Level 1 Depth / Length	15.4 in 391 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Effective Date	19980621
Flammability Hazard Rating	Flame Retardant
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	PLASTIC CONDUIT
Product Type	Thin-Wall Heat Shrinkable Tubing
RoHS Date	9AKK108466A3883
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin

Certificates and Declarations

Data Sheet, Technical Information	MLP375-0-BG
-----------------------------------	-------------

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
ETIM 8	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

