NENV0505 1/3



PRODUCT-DETAILS

NENV0505 EX STR MALE FTNG NC25,M25 BLK



| General Information | |
|------------------------|--|
| Extended Product Type | NENV0505 |
| Product ID | 7TCA297120R0341 |
| EAN | 5011949239876 |
| Catalog Description | EX STR MALE FTNG NC25,M25 BLK |
| Long Description | Conduit Fitting, Straight with External Male Thread, Conduit Size 25mm, M25 Thread, Minimum Bore 23mm, Suitable for Unbraided Nylon Conduit, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black |
| Additional Information | |
| Application | For Indoor and Outdoor Applications |
| Product Type | Straight Conduit Fitting with Male Thread |
| | |
| Ordering | |
| EAN | 5011949239876 |
| | |

NENV0505 2/3

| Number of Batteries | |
|--|---|
| Color | Black |
| Material | Modified Nylon 12 with Nickel Plated Threads |
| Size | Conduit Size 25mm, M25 Threac |
| Environmental | |
| | |
| WEEE Category | Product Not in WEEE Scope |
| | |
| Container Information | |
| | 140 EA |
| Container Information Package Level 1 Units Package Level 1 Height | 302.26 mm |
| Package Level 1 Units | 140 EA 302.26 mm 11.9 in 210.82 mm 8.3 in |

| Certificates and Declarations | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK106930A7762 |
| Instructions and Manuals | NENV0505 |
| Declaration of Conformity | 9AKK107680A0674 |

| Classifications | |
|-----------------|---|
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| LINSDSC | 30121311 |

Categories

 $Low\ Voltage\ Products\ and\ Systems \to Installation\ Products \to Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \to Flexible\ Cable\ Protection\ Systems$

NENV0505 3/3

