



PRODUCT-DETAILS

NENZ0404S/P3

EX STRNRELIEF FTNG NC20,M20 6.5-9.5



General Information	
Extended Product Type	NENZ0404S/P3
Product ID	7TCA297120R0370
EAN	5011949240162
Catalog Description	EX STRNRELIEF FTNG NC20,M20 6.5-9.5
Long Description	Conduit Fitting with Strain Relief, Straight with External Male Thread, Conduit Size 20mm, M20 Thread, Minimum Bore 17mm, Suitable for Unbraided Nylon Conduit, Clamping Range 6.5 to 9.5 K, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black

Additional Information	
Application	For Indoor and Outdoor Applications
Product Type	Straight Conduit Fitting with Male Thread and Strain Relief

Ordering	
EAN	5011949240162

Technical	
Number of Batteries	0
Color	Black
Material	Modified Nylon 12 with Nickel Plated Threads
Size	Conduit Size 20mm ; M20 Thread

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	10 piece
Package Level 1 Height	7.9 in 201 mm
Package Level 1 Depth / Length	8.3 in 211 mm
Package Level 1 Width	11.9 in 302 mm

Certificates and Declarations	
Data Sheet, Technical Information	9AKK106930A7766
Instructions and Manuals	NENZ0404S/P3
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121311

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	



Product image
not available