



PRODUCT-DETAILS**NENZ0707S/P1****EX STRN RELIEF FTNG NC40,M40 20-25**Product image
not available

General Information

Extended Product Type	NENZ0707S/P1
Product ID	7TCA297120R0377
EAN	5011949240230
Catalog Description	EX STRN RELIEF FTNG NC40,M40 20-25
Long Description	Conduit Fitting with Strain Relief, Straight with External Male Thread, Conduit Size 40mm, M40 Thread, Minimum Bore 36mm, Suitable for Unbraided Nylon Conduit, Clamping Range 20.0 to 25.0 K, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black

Additional Information

Application	For Indoor and Outdoor Applications
Product Type	Straight Conduit Fitting with Male Thread and Strain Relief

Ordering

EAN	5011949240230
-----	---------------

Technical

Number of Batteries	0
Color	Black
Material	Modified Nylon 12 with Nickel Plated Threads
Size	Conduit Size 40mm ; M40 Thread

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	10 piece
Package Level 1 Height	7.9 in 201 mm
Package Level 1 Depth / Length	8.3 in 211 mm
Package Level 1 Width	11.9 in 302 mm

Certificates and Declarations

Data Sheet, Technical Information	9AKK106930A7766
Instructions and Manuals	NENZ0707S/P1
Declaration of Conformity - CE	9AKK107680A0674

Classifications

ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121311

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available