



---

**PRODUCT-DETAILS****NENZ0808S/P2****EX STRN RELIEF FTNG NC50,M50 32-36**

Product image  
not available

---

**General Information**

Extended Product Type	NENZ0808S/P2
Product ID	7TCA297120R0379
EAN	5011949240254
Catalog Description	EX STRN RELIEF FTNG NC50,M50 32-36
Long Description	Conduit Fitting with Strain Relief, Straight with External Male Thread, Conduit Size 50mm, M50 Thread, Minimum Bore 48mm, Suitable for Unbraided Nylon Conduit, Clamping Range 32.0 to 36.0 K, Approved for Zone 1 and 2, Zone 21 and 22, IP68 Rating, Modified Nylon 12 with Nickel Plated Threads, Black

---

**Additional Information**

Application	For Indoor and Outdoor Applications
Product Type	Straight Conduit Fitting with Male Thread and Strain Relief

---

**Ordering**

EAN	5011949240254
-----	---------------

---

---

**Technical**

Number of Batteries	0
Color	Black
Material	Modified Nylon 12 with Nickel Plated Threads
Size	Conduit Size 50mm ; M50 Thread

---

**Environmental**

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

---

**Container Information**

Package Level 1 Units	10 piece
Package Level 1 Height	7.9 in 201 mm
Package Level 1 Depth / Length	8.3 in 211 mm
Package Level 1 Width	11.9 in 302 mm

---

**Certificates and Declarations**

Data Sheet, Technical Information	9AKK106930A7766
Instructions and Manuals	NENZ0808S/P2
Declaration of Conformity - CE	9AKK107680A0674

---

**Classifications**

ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121311

---

**Categories**

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available