



PRODUCT-DETAILS

NKNZ-M253/P5

FTNG STR M25NW23 PA6/BR 9-13 BLK



| General Information | |
|-----------------------|---|
| Extended Product Type | NKNZ-M253/P5 |
| Product ID | 7TCA292000R0188 |
| EAN | 7630030260759 |
| Catalog Description | FTNG STR M25NW23 PA6/BR 9-13 BLK |
| Long Description | Straight Connector with Strain Relief, Halogenfree Polyamide 6, Nickel-Plated Brass Thread, Thread Size M25x1.5, Conduit Size NW 23, Clamping Range 9.0 - 13.0k, IP68 and IP69 Certified, Black |

| Additional Information | |
|------------------------|---------------------|
| Product Type | Connectors-Straight |

| Ordering | |
|----------|---------------|
| EAN | 7630030260759 |
| UPC | 786210059266 |

| Technical | |
|---------------------|--|
| Number of Batteries | 0 |
| Color | Black |
| Material | Polyamide 6 with Nickel Plated Brass Threads |
| Size | NW23 , M25x1.5 Thread |

| Environmental | |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information | |
|--------------------------------|---------------------|
| Package Level 1 Units | 30 EA |
| Package Level 1 Height | 66.04 mm 2.6 in |
| Package Level 1 Depth / Length | 134.62 mm 5.3 in |
| Package Level 1 Width | 99.06 mm 3.9 in |

| Certificates and Declarations | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | NKNZ-M253/P5 |
| Instructions and Manuals | NKNZ-M253/P5 |
| Declaration of Conformity - CE | 9AKK107680A0674 |

| Classifications | |
|-----------------|---|
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC | 39121420 |

| Categories | |
|---|--|
| Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems | |

