NKNZ-M406/P1 1/3



PRODUCT-DETAILS

NKNZ-M406/P1 FTNG PA6/BR NW36 M40 20-25



General Information	
Extended Product Type	NKNZ-M406/P1
Product ID	7TCA292000R5867
EAN	7630030297151
Catalog Description	FTNG PA6/BR NW36 M40 20-25
Long Description	Straight Connector with Strain Relief, Halogenfree Polyamide 6, Nickel-Plated Brass Thread, Thread Size M40x1.5, Conduit Size NW36, Clamping Range 20.0 - 25.0, IP68 and IP69 Certified, Black

Additional Information

Product Type Connectors-Straight

Ordering	
EAN	7630030297151
UPC	786210170343

NKNZ-M406/P1 2/3

Technical	
Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW36 , M40x1.5 Thread

Environmental

WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	20 EA
Package Level 1 Height	100.076 mm 3.94 in
Package Level 1 Depth /	350.012 mm
Length	13.78 in
Package Level 1 Width	279.908 mm
-	11.02 in

Certificates and Declarations

Data Sheet, Technical Information	NKNZ-M406/P1
Instructions and Manuals	NKNZ-M406/P1
Declaration of Conformity - CE	9AKK107680A0674

Classifications

ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121420

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Lost and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

NKNZ-M406/P1 3/3

