



PRODUCT-DETAILS

NVNZ-M162GT-10

FITTING PA6/BR NW12 M16 IP68 BLK



| General Information | |
|-----------------------|--|
| Extended Product Type | NVNZ-M162GT-10 |
| Product ID | 7TCA292000R0259 |
| EAN | 7630030255236 |
| Catalog Description | FITTING PA6/BR NW12 M16 IP68 BLK |
| Long Description | VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68GT - Thread M16x1.5, Conduit Size NW 12, Thread Length 10 Millimeters, with Sealing Insert, Color Black |

| Additional Information | |
|------------------------|--|
| Application | Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas |
| Product Type | Fittings for Nylon Flexible Conduits |

| Ordering | |
|----------|---------------|
| EAN | 7630030255236 |
| UPC | 786210171364 |

| Technical | |
|---------------------|--|
| Number of Batteries | 0 |
| Color | Black |
| Material | Polyamide 6 with Nickel Plated Brass Threads |
| Size | NW12 ; M16x1.5 |

| Environmental | |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information | |
|--------------------------------|------------------------|
| Package Level 1 Units | 50 EA |
| Package Level 1 Height | 100.076 mm 3.94 in |
| Package Level 1 Depth / Length | 350.012 mm 13.78 in |
| Package Level 1 Width | 279.908 mm 11.02 in |

| Certificates and Declarations | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | NVNZ-M162GT-10 |
| Instructions and Manuals | NVNZ-M162GT-10 |
| Declaration of Conformity - CE | 9AKK107680A0674 |

| Classifications | |
|-----------------|---|
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC | 39121719 |

| Categories | |
|---|--|
| Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems | |



Product image
not available