



PRODUCT-DETAILS

NVNZ-M202GT/P1L

FTNG PA6/BR NW12 M20 4-6.5 BLK 15MM



Product image
not available

General Information	
Extended Product Type	NVNZ-M202GT/P1L
Product ID	7TCA292000R0261
EAN	7630030255175
Catalog Description	FTNG PA6/BR NW12 M20 4-6.5 BLK 15MM
Long Description	VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68GT - Thread M20x1.5, Thread Length 15 Millimeters, Conduit Size NW 12, Clamping Range 4.0-6.5, with Sealing Insert, Color Black

Additional Information	
Application	Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas
Product Type	Fittings for Nylon Flexible Conduits

Ordering	
EAN	7630030255175
UPC	786210171418

Technical	
Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW12 ; M20x1.5

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	50 EA
Package Level 1 Height	100.076 mm 3.94 in
Package Level 1 Depth / Length	350.012 mm 13.78 in
Package Level 1 Width	279.908 mm 11.02 in

Certificates and Declarations	
Data Sheet, Technical Information	NVNZ-M202GT/P1L
Instructions and Manuals	NVNZ-M202GT/P1L
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121719

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	



Product image
not available