



PRODUCT-DETAILS

NVNZ-M329GT/P3

FTNG STR M32NW29 PA6/BR 17-20.568GT



General Information	
Extended Product Type	NVNZ-M329GT/P3
Product ID	7TCA292000R0276
EAN	7630030254512
Catalog Description	FTNG STR M32NW29 PA6/BR 17-20.568GT
Long Description	Straight Connector with Strain Relief, Halogenfree Polyamide 6, Thread Size M32x1.5, Conduit Size NW 29, Clamping Range 17.0 - 20.5 Millimeters, IP68GT Certified, One-Piece with Integrated Sealing Cap and Pre-Installed Locking Clip, Black

Additional Information	
Application	Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas
Product Type	Fittings for Nylon Flexible Conduits

Ordering	
EAN	7630030254512
UPC	786209918208

Technical	
Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW29 ; M32x1.5

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	20 EA
Package Level 1 Height	64.262 mm 2.53 in
Package Level 1 Depth / Length	388.62 mm 15.3 in
Package Level 1 Width	287.02 mm 11.3 in

Certificates and Declarations	
Data Sheet, Technical Information	NVNZ-M329GT/P3
Instructions and Manuals	NVNZ-M329GT/P3
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121719

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

