



PRODUCT-DETAILS

# NVNZ-M329S/P3

## FTNG STR M32NW29 PA6/BR 17-20.5 BLK



| General Information   |                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | NVNZ-M329S/P3                                                                                                                                                        |
| Product ID            | 7TAA292150R0754                                                                                                                                                      |
| EAN                   | 7630030254444                                                                                                                                                        |
| Catalog Description   | FTNG STR M32NW29 PA6/BR 17-20.5 BLK                                                                                                                                  |
| Long Description      | VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68 - Thread M32x1.5, Conduit Size NW 29, Clamping Range 17.0-20.5, with Sealing Insert, Color Black |

| Additional Information |                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------|
| Application            | Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas |
| Product Type           | Fittings for Nylon Flexible Conduits                                                               |

| Ordering |               |
|----------|---------------|
| EAN      | 7630030254444 |
| UPC      | 786209964878  |

| Technical           |                                              |
|---------------------|----------------------------------------------|
| Number of Batteries | 0                                            |
| Color               | Black                                        |
| Material            | Polyamide 6 with Nickel Plated Brass Threads |
| Size                | NW29 , M32x1.5                               |

| Environmental |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information          |              |
|--------------------------------|--------------|
| Package Level 1 Units          | 20 EA        |
| Package Level 1 Height         | 0 mm<br>0 in |
| Package Level 1 Depth / Length | 0 mm<br>0 in |
| Package Level 1 Width          | 0 mm<br>0 in |

| Certificates and Declarations     |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | NVNZ-M329S/P3   |
| Instructions and Manuals          | NVNZ-M329S/P3   |
| Declaration of Conformity - CE    | 9AKK107680A0674 |

| Classifications |                                                         |
|-----------------|---------------------------------------------------------|
| ETIM 8          | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC          | 39121719                                                |

| Categories                                                                                                                                    |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--|
| Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems |  |

