



PRODUCT-DETAILS

NVNZ-M406GT/P2
FTNG STR M40 NW36 PA6/BR 24-28 68GT



General Information	
Extended Product Type	NVNZ-M406GT/P2
Product ID	7TCA292000R0280
EAN	7630030254390
Catalog Description	FTNG STR M40 NW36 PA6/BR 24-28 68GT
Long Description	Straight Connector with Strain Relief, Halogenfree Polyamide 6, Thread Size M40x1.5, Conduit Size NW 36, Clamping Range 24.0 - 28.0 Millimeters, IP68GT Certified, One-Piece with Integrated Sealing Cap and Pre-Installed Locking Clip, Black
Additional Information	
Application	Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas
Product Type	Fittings for Nylon Flexible Conduits
Ordering	
EAN	7630030254390
UPC	786209896490

Technical

Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW36 : M40x1.5

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	20 EA
Package Level 1 Height	57.15 mm 2.25 in
Package Level 1 Depth / Length	387.35 mm 15.25 in
Package Level 1 Width	284.734 mm 11.21 in

Certificates and Declarations

Data Sheet, Technical Information	NVNZ-M406GT/P2
Instructions and Manuals	NVNZ-M406GT/P2
Declaration of Conformity - CE	9AKK107680A0674

Classifications

ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121719

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

