



PRODUCT-DETAILS

NVNZ-M506GT/P3

FITTING PA6/BR NW36 M50 32-36



Product image not available

| General Information | |
|-----------------------|--|
| Extended Product Type | NVNZ-M506GT/P3 |
| Product ID | 7TCA292000R0289 |
| EAN | 7630030254130 |
| Catalog Description | FITTING PA6/BR NW36 M50 32-36 |
| Long Description | VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68GT - Thread M50x1.5, Conduit Size NW 36, Clamping Range 32.0-36.0, with Sealing Insert, Color Black |

| Additional Information | |
|------------------------|--|
| Application | Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas |
| Product Type | Fittings for Nylon Flexible Conduits |

| Ordering | |
|----------|---------------|
| EAN | 7630030254130 |
| UPC | 786210171845 |

Technical

| | |
|---------------------|--|
| Number of Batteries | 0 |
| Color | Black |
| Material | Polyamide 6 with Nickel Plated Brass Threads |
| Size | NW36 , M50x1.5 |

Environmental

| | |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |
|---------------|---------------------------|

Container Information

| | |
|--------------------------------|------------------------|
| Package Level 1 Units | 20 EA |
| Package Level 1 Height | 100.076 mm 3.94 in |
| Package Level 1 Depth / Length | 350.012 mm 13.78 in |
| Package Level 1 Width | 279.908 mm 11.02 in |

Certificates and Declarations

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | NVNZ-M506GT/P3 |
| Instructions and Manuals | NVNZ-M506GT/P3 |
| Declaration of Conformity - CE | 9AKK107680A0674 |

Classifications

| | |
|--------|---|
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC | 39121719 |

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available