



PRODUCT-DETAILS

NVNZ-M506S/P3-L

FTNG STR M50 NW36 PA6/BR 32-36 LONG



| General Information | |
|-----------------------|---|
| Extended Product Type | NVNZ-M506S/P3-L |
| Product ID | 7TAA292150R0780 |
| EAN | 7630030254055 |
| Catalog Description | FTNG STR M50 NW36 PA6/BR 32-36 LONG |
| Long Description | VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68 - Long Thread M50x1.5, Conduit Size NW 36, Clamping Range 32.0-36.0, with Sealing Insert, Color Black |

| Additional Information | |
|------------------------|--|
| Application | Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas |
| Product Type | Fittings for Nylon Flexible Conduits |

| Ordering | |
|----------|---------------|
| EAN | 7630030254055 |
| UPC | 786209965127 |

| | |
|---------------------|--|
| Technical | |
| Number of Batteries | 0 |
| Color | Black |
| Material | Polyamide 6 with Nickel Plated Brass Threads |
| Size | NW36 , M50x1.5 |

| | |
|----------------------|---------------------------|
| Environmental | |
| WEEE Category | Product Not in WEEE Scope |

| | |
|--------------------------------|-------------------------|
| Container Information | |
| Package Level 1 Units | 40 EA |
| Package Level 1 Height | 200 mm 7.874 in |
| Package Level 1 Depth / Length | 399.999 mm 15.748 in |
| Package Level 1 Width | 299.999 mm 11.811 in |

| | |
|--------------------------------------|-----------------|
| Certificates and Declarations | |
| Data Sheet, Technical Information | NVNZ-M506S/P3-L |
| Instructions and Manuals | NVNZ-M506S/P3-L |
| Declaration of Conformity - CE | 9AKK107680A0674 |

| | |
|------------------------|---|
| Classifications | |
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC | 39121719 |

| | |
|---|--|
| Categories | |
| Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems | |

