NVNZ-M508GT/P3 1/3



PRODUCT-DETAILS

NVNZ-M508GT/P3FITTING PA6/BR NW48 M50 36-40



General Information	
Extended Product Type	NVNZ-M508GT/P3
Product ID	7TCA292000R5576
EAN	7630030293733
Catalog Description	FITTING PA6/BR NW48 M50 36-40
Long Description	VNZ Connector Straight, Metric Metal Thread with Strain Relief IP68GT - Thread M50x1.5, Conduit Size NW 48, Clamping Range 36.0-40.0, with Sealing Insert, Color Black

Additional Information	
Application	Use In Railway Vehicle and Heavy Machine Construction and for the Separation of Damp and Dry Areas
Product Type	Fittings for Nylon Flexible Conduits

Ordering	
EAN	7630030293733
UPC	786210171869

NVNZ-M508GT/P3 2/3

Technical	
Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW48, M50x1.5

Environmental

WEEE Category Product Not in WEEE Scope

Container Information	
Package Level 1 Units	10 EA
Package Level 1 Height	100.076 mm 3.94 in
Package Level 1 Depth / Length	350.012 mm 13.78 in
Package Level 1 Width	279.908 mm 11.02 in

Certificates and Declarations	
Data Sheet, Technical Information	NVNZ-M508GT/P3
Instructions and Manuals	NVNZ-M508GT/P3
Declaration of Conformity - CE	9AKK107680A0674

Classifications	
ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121719

Categories

 $Low\ Voltage\ Products\ \rightarrow\ Lost and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

NVNZ-M508GT/P3 3/3

