NVNZ-P488S 1/3



PRODUCT-DETAILS

NVNZ-P488S FTNG STR PG48 NW48 PA6/BR W/INS



EAN Catalog Description FTNG STR PG48 NW48 P. Long Description VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, NW 48, Clamping Range 34.0-44.0, with Sealing Inser Additional Information Application Use In Railway Vehicle and Heavy Machine Product Type Fittings for Nylon Flex	Extended Product Type	NVNZ-P488S
Catalog Description FTNG STR PG48 NW48 P VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48,	Product ID	7TAA292150R0860
Long Description VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, NW 48, Clamping Range 34.0-44.0, with Sealing Inser Additional Information Application Use In Railway Vehicle and Heavy Machine Product Type Fittings for Nylon Flex	EAN	7630030253102
Additional Information Application Product Type NW 48, Clamping Range 34.0-44.0, with Sealing Inser NW 48, Clamping Range 34.0-44.0, with Sealing Inser	Catalog Description	FTNG STR PG48 NW48 PA6/BR W/INS
Application Use In Railway Vehicle and Heavy Machine Product Type Fittings for Nylon Flex	Long Description	VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, Conduit Size NW 48, Clamping Range 34.0-44.0, with Sealing Insert, Color Black
Application Use In Railway Vehicle and Heavy Machine Product Type Fittings for Nylon Flex		
Product Type Fittings for Nylon Flex	Additional Information	
Oudering		Use In Railway Vehicle and Heavy Machine Construction
	Application	Use In Railway Vehicle and Heavy Machine Construction Fittings for Nylon Flexible Conduits
<u>Ordering</u>	Application Product Type	,

<u>UPC</u>

786209965943

NVNZ-P488S 2/3

Technical	
Number of Batteries	
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW48 , PG48
Environmental	
WEEE Category	Product Not in WEEE Scope
Container Information	
Package Level 1 Units	20 EA
Package Level 1 Height	219.989 mm 8.661 in
Package Level 1 Depth / Length	399.999 mm 15.748 in
Package Level 1 Width	299.999 mm 11.811 in
Certificates and Declarations	
Data Sheet, Technical Information	NVNZ-P488S
Instructions and Manuals	NVNZ-P488S
Declaration of Conformity - CE	9AKK107680A0674
Classifications	
Classifications	
ETIM 8	EC001176 - Screw connection for corrugated plastic hose
UNSPSC	39121719

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \to\ Installation\ Products\ \to\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \to\ Flexible\ Cable\ Protection\ Systems$

NVNZ-P488S 3/3

