NVNZ-P488S/P1 1/3



PRODUCT-DETAILS

NVNZ-P488S/P1 FTNG STR PG48 NW48 PA6/BR 32-35 BLK



7TAA292150R0862 7630030253072 FTNG STR PG48 NW48 PA6/BR 32-35 BLK VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, Conduit Size NW 48, Clamping Range 32.0-35.0, with Sealing Insert, Color Black
FTNG STR PG48 NW48 PA6/BR 32-35 BLK VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, Conduit Size
VNZ Connector Straight, PG Metal Thread with Strain Relief IP68 - Thread 48, Conduit Size
Use In Railway Vehicle and Heavy Machine Construction
Fittings for Nylon Flexible Conduits

EAN

<u>UPC</u>

7630030253072

786209965967

NVNZ-P488S/P1 2/3

Technical	
Number of Batteries	0
Color	Black
Material	Polyamide 6 with Nickel Plated Brass Threads
Size	NW48 , PG48
Environmental	
WEEE Category	Product Not in WEEE Scope
Container Information	
Package Level 1 Units	10 EA
Package Level 1 Height	0 mm 0 in
Package Level 1 Depth / Length	0 mm 0 in
Package Level 1 Width	0 mm 0 in
Certificates and Declarations	
Data Sheet, Technical Information	NVNZ-P488S/P1
Instructions and Manuals	NVNZ-P488S/P1
Declaration of Conformity - CE	9AKK107680A0674
Classifications	
	F0004470 0
ETIM 8 UNSPSC	EC001176 - Screw connection for corrugated plastic hose 39121719

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \to\ Installation\ Products\ \to\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \to\ Flexible\ Cable\ Protection\ Systems$

NVNZ-P488S/P1 3/3

