NVWV-P299 1/3



PRODUCT-DETAILS

NVWV-P299 FTNG 90D PG29 NW29 PA6/BR IP68 BLK



| General Information | |
|-----------------------|---|
| Extended Product Type | NVWV-P299 |
| Product ID | 7TAA292150R0889 |
| EAN | 7630030252334 |
| Catalog Description | FTNG 90D PG29 NW29 PA6/BR IP68 BLK |
| Long Description | VWV Connector 90 Degree Elbow, PG Metal Thread IP68 - Thread 29, Fits to Conduit Size NW/Metric 29/32, Color Black |

| Additional Information | |
|------------------------|---|
| Application | Use In Railway Vehicle and Heavy Machine Construction |
| Product Type | Fittings for Nylon Flexible Conduits |

| Ordering | |
|----------|---------------|
| EAN | 7630030252334 |
| UPC | 786209966346 |

NVWV-P299 2/3

| Technical | |
|---------------------|--|
| Number of Batteries | 0 |
| Color | Black |
| Material | High-Grade Specially Formulated Polyamide, Thread Made of Nickel-Plated Brass |
| Size | PG29 |

Environmental

| Container Information | |
|-------------------------|------------|
| Package Level 1 Units | 60 EA |
| Package Level 1 Height | 200 mm |
| | 7.874 in |
| Package Level 1 Depth / | 399.999 mm |
| Length | 15.748 in |
| Package Level 1 Width | 299.999 mm |
| | 11.811 in |

| Certificates and Declarations | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | NVWV-P299 |
| Instructions and Manuals | NVWV-P299 |
| Declaration of Conformity - CE | 9AKK107680A0674 |

| Classifications | |
|-----------------|---|
| ETIM 8 | EC001176 - Screw connection for corrugated plastic hose |
| UNSPSC | 39131717 |

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

NVWV-P299 3/3

