



PRODUCT-DETAILS

OT160EVFCC3B

OT160EVFCC3B Encl. Switch Disconnecter



General Information	
Extended Product Type	OT160EVFCC3B
Product ID	1SCA148615R1001
EAN	6417019781457
Catalog Description	OT160EVFCC3B Encl. Switch Disconnector
Long Description	Encl. Switch Disconnecter, 3-p. 415V AC23 160A, 88kW. Plastic enclosure. IP65. Black Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included.

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340015M0004

Dimensions

Product Net Width	280 mm
Product Net Height	380 mm
Product Net Depth / Length	130 mm
Product Net Weight	4 kg

Technical

Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A (P _e)	(380 ... 415 V) 88 kW (500 V) 112 kW (690 V) 144 kW
Conventional Thermal Current (I _{the})	Fully Enclosed 160 A
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(1000 V AC) 30 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 8 kA
Rated Conditional Short-Circuit Current (I _{nc})	40.5 kA
Pollution Degree	3
Handle Color	Black
Handle Type	Pistol handle
Position of Line Terminals	Top In - Bottom Out
Standards	IEC 60947-1, -3
Number of Poles	3
Neutral Type	Detachable neutral
Connecting Capacity	Hole Diameter 8 mm

Main Circuit	Screw Clamp / PE Terminal 2pc,10 ... 70 mm²
Recommended Screw Driver	Main Circuit M8
Cable Entry Position	Top/Bottom
Cable Outlets Per Side	II-flange / II-flange
Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK08
Enclosure Type	Fibox
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Terminal Type	Bolt
Tightening Torque	Main Circuit 6 N·m

Technical UL/CSA

Recommended Screw Driver	Main Circuit M8
Tightening Torque	Main Circuit 6 N·m

Environmental

RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	1SCC340095D0201

Certificates and Declarations

Declaration of Conformity - CE	1SCC340001D2703
REACH Declaration	1SCC340076D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	295 mm
Package Level 1 Depth / Length	510 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	5.1 kg
Package Level 1 EAN	6417019781457

Classifications

Object Classification Code	Q
----------------------------	---

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

