



PRODUCT-DETAILS

OT4000E04

OT4000E04 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT4000E04
Product ID	1SCA124855R1001
EAN	6417019551951
Catalog Description	OT4000E04 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector, handle and shaft are not included, <u>terminal bolt kit included</u>

Circular Value

Conflict Minerals	9AKK108467A5658
Reporting Template (CMRT)	1SCC301124M0201
End of Life Instructions	1SCC301269D0201
Environmental Information	1SCC301308D0201
Environmental Product Declaration - EPD	1SCC011021D0201
REACH Declaration	1SCC011020D0201
RoHS Information	1SCC011025D0201
Toxic Substances Control Act - TSCA	

Eco Transparency

Environmental Product
Declaration - EPD

ISCC301308D0201

Ordering

Minimum Order Quantity

1 piece

Customs Tariff Number

85365080

Country of Origin

Finland (FI)

Popular Downloads

Data Sheet, Technical
Information

ISCC301020C0201

Instructions and Manuals

ISCC301082M0206

Mechanical Drawings

OT4000E04

Environmental Product
Declaration - EPD

ISCC301308D0201

End of Life Instructions

ISCC301124M0201

Dimensions

Product Net Width

654 mm

Product Net Height

410 mm

Product Net Depth /
Length

146 mm

Product Net Weight

47.5 kg

Technical

Rated Operational Current
AC-21B (I_e)

(380 ... 415 V) 3800 A

Rated Operational Current
AC-22B (I_e)

(380 ... 415 V) 3800 A

Conventional Free-air
Thermal Current (I_{th}) $\Theta = 40$ °C 3800 ARated Impulse Withstand
Voltage (U_{imp})

8 kV

Rated Insulation Voltage
(U_i)

acc. to IEC/EN 60664-1 1000 V

Rated Operational Voltage

Main Circuit 1000 V

Rated Short-Circuit
Making Capacity (I_{cm})

(690 V) 176 kA

Rated Short-time
Withstand Current Low
Voltage (I_{cw})

for 1 s 80 kA

Power Loss

at Rated Operating Conditions per Pole 130 W

Pollution Degree

3

Handle Type

Handle and shaft not included

Fourth Pole Position

Right Side

Fourth Pole Type

Switched - Simultaneous Function

Switches Operating
Mechanism

Mechanism at the End of the Switch

Distance Between Phases

04 (Left Side)

Position of Line Terminals

Standard

Top In - Bottom Out

Bottom In - Top Out

Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Mechanical Durability	5000
Lock Type	No

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
-------------------	--------------------------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC301269D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Certificates and Declarations

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301211D2701
DNV GL Certificate	1SCC301184D0203
REACH Declaration	1SCC011021D0201
UL Certificate	No certification needed
VDE Certificate	No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	435 mm
Package Level 1 Depth / Length	673 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	49.9 kg
Package Level 1 EAN	6417019551951

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

