



PRODUCT-DETAILS

OT400DFCC4B

OT400DFCC4B Enclosed Switch Disconnecter



| General Information | |
|-----------------------|---|
| Extended Product Type | OT400DFCC4B |
| Product ID | 1SCA022609R5480 |
| EAN | 6417019198477 |
| Catalog Description | OT400DFCC4B Enclosed Switch Disconnector |
| Long Description | Encl. Switch Disconnecter, 4-p. 415V AC23 400A, 230kW. Plastic enclosure. IP65. Black Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OT series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries knock out types for II-flanges. Cables can be inserted from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be defeated. N and PE terminals included. |

| Circular Value | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |
| RoHS Information | 1SCC340075D0201 |

Toxic Substances
Control Act - TSCA

1SCC340095D0201

Ordering

| | |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363090 |
| Country of Origin | Finland (FI) |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC340015C0201 |
| Instructions and Manuals | 1SCC340015M0004 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 380 mm |
| Product Net Height | 840 mm |
| Product Net Depth / Length | 180 mm |
| Product Net Weight | 13.55 kg |

Technical

| | |
|---|---|
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 400 A (690 V) 400 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 230 kW (500 V) 280 kW (690 V) 400 kW |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 400 A |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 1000 V |
| Rated Operational Voltage | Main Circuit 1000 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (1000 V AC) 65 kA |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 15 kA |
| Rated Conditional Short-Circuit Current (I_{nc}) | 61.5 kA |
| Power Loss | at Rated Operating Conditions per Pole 10 W |
| Pollution Degree | 3 |
| Handle Color | Black |
| Handle Type | Pistol handle |
| Standards | IEC 60947-1, -3 |
| Number of Poles | 4 |
| Neutral Type | Switchable neutral |
| Connecting Capacity Main Circuit | Hole Diameter 10 mm Screw Clamp / PE Terminal 4pc,25 ... 120 mm ² |

| | |
|------------------------------------|------------------------|
| Recommended Screw Driver | Main Circuit M10 |
| Cable Entry Position | Top/Bottom |
| Cable Outlets Per Side | II-flange / II-flange |
| Degree of Protection | acc. to IEC 60529 IP65 |
| Impact Resistance Rating | Housing IK08 |
| Enclosure Material | Plastic |
| Maximum Mounted Auxiliary Contacts | 2 NO, 2 NC |
| Mounted Auxiliary Contacts | 0 NO, 0 NC |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Tightening Torque | Main Circuit 44 N·m |

Technical UL/CSA

| | |
|--------------------------|---------------------|
| Recommended Screw Driver | Main Circuit M10 |
| Tightening Torque | Main Circuit 44 N·m |

Environmental

| | |
|-------------------------------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC340025D2704 |
| REACH Declaration | 1SCC340076D0201 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 415 mm |
| Package Level 1 Depth / Length | 910 mm |
| Package Level 1 Height | 325 mm |
| Package Level 1 Gross Weight | 16 kg |
| Package Level 1 EAN | 6417019198477 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 7 | EC000216 - Switch disconnecter |
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |

| | |
|---------------|---|
| eClass | V11.1 : 27371403 |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

