



PRODUCT-DETAILS

# OT60FT3

## OT60FT3 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT60FT3
Product ID	1SCA105081R1001
EAN	6417019392110
Catalog Description	OT60FT3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, door mounted, switch-diconnector / non-fusible diconnect switch with front protected clamp terminals, handle and shaft are not included

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Product Declaration - EPD	1SCC301280D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Eco Transparency

Environmental Product Declaration - EPD	1SCC301280D0201
---	-----------------

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301060M0004
Mechanical Drawings	1SCC301470F0001 1SCC301469F0001 OT125FT3.igs
Environmental Product Declaration - EPD	1SCC301280D0201

Dimensions

Product Net Width	70 mm
Product Net Height	100 mm
Product Net Depth / Length	66.5 mm
Product Net Weight	0.42 kg

Technical

Rated Operational Current AC-22A (I <sub>e</sub> )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I <sub>e</sub> )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 40 A
Rated Operational Power AC-23A (P <sub>e</sub> )	(380 ... 415 V) 37 kW (500 V) 37 kW (690 V) 37 kW
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> )	(690 V) 3.6 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 1 s 2.5 kA
Power Loss	at Rated Operating Conditions per Pole 1.6 W
Pollution Degree	3

Handle Type	Handle and shaft not included
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 98 / CSA C22.2 NO.4
Special Functions	No
Mounting Type	Door mounting
Number of Poles	3
Cable Cross-Section	Cu 2.5 ... 25 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 6.2 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	60 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 3 Hp (240 V AC) Single Phase 7.5 Hp (220 ... 240 V AC) Three Phase 20 Hp (440 ... 480 V AC) Three Phase 40 Hp (550 ... 600 V AC) Three Phase 40 Hp
Tightening Torque	acc. IEC 60947-1 6.2 N·m

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Certificates and Declarations

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301010D0201
REACH Declaration	1SCC011021D0201
UL Certificate	cULus certificate OT30-125
VDE Certificate	No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	71 mm
Package Level 1 Height	76 mm
Package Level 1 Gross Weight	0.44 kg
Package Level 1 EAN	6417019392110

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

