



PRODUCT-DETAILS**OTDC1000FV22****OTDC1000FV22 DC Switch-disconnector**

General Information

Extended Product Type	OTDC1000FV22
Product ID	1SCA161288R1001
EAN	6417019913902
Catalog Description	OTDC1000FV22 DC Switch-disconnector
Long Description	<p>A fully optimized four-pole DC switch-disconnector for 1500V utility-scale photovoltaic power plants covering 315-1000A current range. The new design offers both a size reduction and an increase in efficiency and performance to help manufacturers adapt to the industry's rapid adoption of 1500V DC solutions.</p> <p>The four-pole 1500V DC concept helps manufacturers improve system efficiency, reducing switch losses. The compact size of the new OTDC range makes it possible for manufacturers to reduce the size of combiner boxes and inverters.</p> <p>Main characteristics of this particular OTDC type: Disconnect double PV circuit, Approved according to IEC 60947-1, -3</p>

Circular Value

ABB EcoSolutions	Yes
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 59,09 %
Principles Recyclability	
Rate	

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	1SCC301112M0201
Environmental Product Declaration - EPD	1SCC301247D0201
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Improved Resource Efficiency for Customers	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201
Toxic Substances Control Act - TSCA	1SCC301321D0201

Eco Transparency

Environmental Product Declaration - EPD	1SCC301247D0201
---	-----------------

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85353010
Country of Origin	Finland (FI) India (IN)

Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301102M0201
Mechanical Drawings	OTDC800...1000_F_22_OTDCKIT800FS11.igs OTDC800...1000_F_22_OTDCKIT800FS11.stp 1SCC307779F0201 1SCC307780F0201
Wiring Diagram	1SCC301046K0201
Environmental Product Declaration - EPD	1SCC301247D0201
End of Life Instructions	1SCC301112M0201

Dimensions

Product Frame Size	M
Product Net Width	255.5 mm 10.1 in
Product Net Height	211 mm 8.3 in
Product Net Depth / Length	135 mm 5.3 in
Product Net Weight	9.7 kg 21.3 lb

Technical

Connection Configuration	Single circuit 6c, 6g
Rated Operational Current DC-21B (I_e)	(1500 V) 1000 A
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40^\circ\text{C}$ 1000 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Operational Voltage	1500 V
Rated Short-Circuit Making Capacity (I_{cm})	(1500 V DC) 10 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	(1500 V DC) 10 kA for 1 s 10 kA
Power Loss	at Rated Operating Conditions per Pole 30...32 W
Handle Type	Handle and shaft not included
Positive Opening Operation Torque (Direct Opening Action)	18 ... 30 N·m
Shaft Diameter	12 mm 0.47 in
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Base Mounting
Number of Circuits	1
Number of Poles	4
Terminal Width	30 mm 1.2 in
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B) Switching of single PV string(s) without reverse and overcurrents (DC-PV1)

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC301321D0201

Certificates and Declarations

CCC Certificate	CQC2019010302206498
Declaration of Conformity - CE	1SCC301227D2706
Declaration of Conformity - UKCA	1SCC301313D0201
DNV GL Certificate	1SCC301231D0201
REACH Declaration	1SCC301240D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	270 mm 10.6 in
Package Level 1 Depth / Length	310 mm 12.2 in
Package Level 1 Height	200 mm 7.9 in
Package Level 1 Gross Weight	10 kg 22 lb
Package Level 1 EAN	6417019913902

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors



ABB
Eco
Solutions™