



---

**PRODUCT-DETAILS**

## OTDC250E11

### OTDC250E11 DC Switch-disconnector



---

**General Information**

Extended Product Type	OTDC250E11
Product ID	1SCA125865R1001
EAN	6417019544779
Catalog Description	OTDC250E11 DC Switch-disconnector
Long Description	OTDC250E11 DC Switch-disconnector, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, IEC 1000 VDC 250 A

---

**Circular Value**

ABB EcoSolutions	Yes
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 66,5 %
Principles Recyclability	
Rate	
Conflict Minerals	9AKK108467A5658
Reporting Template (CMRT)	
End of Life Instructions	1SCC301114M0201
Environmental Information	NA

Environmental Product Declaration - EPD	1SCC301248D0201
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Improved Resource Efficiency for Customers	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
REACH Declaration	1SCC301240D0201
RoHS Information	1SCC301239D0201
Toxic Substances Control Act - TSCA	1SCC301321D0201

## Eco Transparency

Environmental Product Declaration - EPD	1SCC301248D0201
---	-----------------

## Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

## Popular Downloads

Data Sheet, Technical Information	1SCC301022C0201
Instructions and Manuals	1SCC301081M0206
Mechanical Drawings	OTDC100_250E11.igs 1SCC307007F0002 1SCC307008F0002
Environmental Product Declaration - EPD	1SCC301248D0201
End of Life Instructions	1SCC301114M0201

## Dimensions

Product Frame Size	51.0
Product Net Width	115.5 mm 4.5 in
Product Net Height	176 mm 6.9 in
Product Net Depth / Length	83.5 mm 3.3 in
Product Net Weight	1.3 kg 2.8 lb

## Technical

Connection Configuration	Single circuit 2a, 2b
Rated Operational Current DC-21B (I <sub>e</sub> )	(1000 V) 250 A
Conventional Free-air Thermal Current (I <sub>th</sub> )	Θ = 40 °C 250 A

Conventional Thermal Current (I <sub>the</sub> )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	12 kV
Rated Insulation Voltage (U <sub>i</sub> )	1500 V
Rated Operational Voltage	1000 V
Rated Short-Circuit Making Capacity (I <sub>cm</sub> )	(1000 V DC) 10 kA
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	(1000 V DC) 10 kA for 1 s 5 kA for 0.1 s 10 kA
Power Loss	at Rated Operating Conditions per Pole 9.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Positive Opening Operation Torque (Direct Opening Action)	5 ... 8 N·m
Shaft Diameter	6 mm 0.24 in
Switches Operating Mechanism	Mechanism Between the Poles 11 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front Operated
Standards	IEC 60947-1, -3
Special Functions	No
Mounting Type	Base mounting
Number of Circuits	1
Number of Poles	2
Degree of Protection	Front IP20
Terminal Type	Lug terminals
Terminal Width	19.5 mm 0.77 in
Utilization	Photovoltaic
Utilization Category	Switching of resistive loads, including moderate overloads - occasional actuation (DC-21B)

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	NA
Toxic Substances Control Act - TSCA	1SCC301321D0201

## Certificates and Declarations

CCC Certificate	CQC2013010302611671
Declaration of Conformity - CE	1SCC301201D2703
Declaration of Conformity - UKCA	1SCC301313D0201
DNV GL Certificate	1SCC301231D0201
REACH Declaration	1SCC301240D0201

---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	96 mm 3.8 in
Package Level 1 Depth / Length	160 mm 6.3 in
Package Level 1 Height	244 mm 9.6 in
Package Level 1 Gross Weight	1.4 kg 3.1 lb
Package Level 1 EAN	6417019544779

---

## Classifications

---

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Switches → DC Switch-Disconnectors



ABB  
**Eco**  
Solutions™