



---

**PRODUCT-DETAILS****OTP125BA4M****OTP125BA4M Enclosed Switch Disconnector**

---

**General Information**

|                       |   |
|-----------------------|---|
| Extended Product Type | OTP125BA4M  |
| Product ID            | 1SCA022812R7510   |
| EAN                   | 6417019274911   |
| Catalog Description   | OTP125BA4M Enclosed Switch Disconnector   |
| Long Description      | <p>Encl. Switch Disconnector, 4-p. 415V AC23 90A, 45kW. Plastic enclosure. IP65. RedYellow Selector handle. Interlocked cover. Defeatable interlocking. The enclosure in the OTP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal.</p> |

---

**Circular Value**

|                           |                 |
|---------------------------|-----------------|
| Conflict Minerals         | 9AKK108467A5658 |
| Reporting Template (CMRT) |                 |
| REACH Declaration         | 1SCC340076D0201 |

|                                     |                 |
|-------------------------------------|-----------------|
| RoHS Information                    | 1SCC340075D0201 |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

## Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85363030     |
| Country of Origin      | Finland (FI) |

## Popular Downloads

|                                   |                    |
|-----------------------------------|--------------------|
| Data Sheet, Technical Information | 1SCC340015C0201    |
| Instructions and Manuals          | 1SCC340002M0012    |
| Mechanical Drawings               | OTPK402014SM50.stp |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 200 mm |
| Product Net Height         | 400 mm |
| Product Net Depth / Length | 140 mm |
| Product Net Weight         | 2.3 kg |

## Technical

|   |  |
|---|--|
| Rated Operational Current AC-22A ( $I_e$ )                  | (380 ... 415 V) 125 A<br>(690 V) 125 A   |
| Rated Operational Current AC-23A ( $I_e$ )                  | (380 ... 415 V) 90 A<br>(500 V) 70 A<br>(690 V) 50 A   |
| Rated Operational Power AC-23A ( $P_e$ )                    | (380 ... 415 V) 45 kW<br>(500 V) 45 kW<br>(690 V) 45 kW  |
| Conventional Thermal Current ( $I_{the}$ )                  | Fully Enclosed 125 A   |
| Rated Insulation Voltage ( $U_i$ )                          | acc. to IEC/EN 60664-1 750 V   |
| Rated Operational Voltage                                   | Main Circuit 750 V   |
| Rated Short-Circuit Making Capacity ( $I_{cm}$ )            | (690 V AC) 3.6 kA  |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | for 1 s 2.5 kA   |
| Power Loss  | at Rated Operating Conditions per Pole 6.3 W   |
| Pollution Degree  | 3  |
| Handle Color  | Red / Yellow   |
| Handle Type   | Selector handle  |
| Standards   | IEC 60947-1, -3  |
| Number of Poles   | 4  |
| Neutral Type  | Fixed and switchable neutral   |
| Connecting Capacity Main Circuit                            | Screw Clamp 10 ... 70 mm <sup>2</sup><br>Screw Clamp / PE Terminal 4pc,10 ... 70 mm <sup>2</sup> |

|                                    |                           |
|------------------------------------|---------------------------|
| Cable Cross-Section                | 10 ... 70 mm <sup>2</sup> |
| Wire Stripping Length              | 20 mm                     |
| Recommended Screw Driver           | Main Circuit Hexagon 4    |
| Cable Entry Position               | Top and/or Bottom         |
| Cable Outlets Per Side             | 2xM50+M16 / 2xM50+M16     |
| Degree of Protection               | acc. to IEC 60529 IP65    |
| Impact Resistance Rating           | Housing IK08              |
| Enclosure Material                 | Plastic                   |
| Maximum Mounted Auxiliary Contacts | 2 NO, 2 NC                |
| Mounted Auxiliary Contacts         | 0 NO, 0 NC                |
| Number of Auxiliary Contacts NC    | 0                         |
| Number of Auxiliary Contacts NO    | 0                         |
| Tightening Torque                  | Main Circuit 6 N·m        |

## Technical UL/CSA

|                          |                        |
|--------------------------|------------------------|
| Wire Stripping Length    | 20 mm                  |
| Recommended Screw Driver | Main Circuit Hexagon 4 |
| Tightening Torque        | Main Circuit 6 N·m     |

## Environmental

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| RoHS Status                         | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201                   |

## Certificates and Declarations

|                                |                 |
|--------------------------------|-----------------|
| BV Certificate                 | 1SCC340018D0204 |
| Declaration of Conformity - CE | 1SCC340003D2704 |
| DNV GL Certificate             | 1SCC340045D0203 |
| REACH Declaration              | 1SCC340076D0201 |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 213 mm        |
| Package Level 1 Depth / Length | 417 mm        |
| Package Level 1 Height         | 197 mm        |
| Package Level 1 Gross Weight   | 2.5 kg        |
| Package Level 1 EAN            | 6417019274911 |

## Classifications

|                            |  |
|----------------------------|--|
| Object Classification Code | Q  |
| ETIM 7                     | EC000216 - Switch disconnector                             |
| ETIM 8                     | EC000216 - Switch disconnector                             |
| ETIM 9                     | EC000216 - Switch disconnector (low voltage)               |
| eClass                     | V11.1 : 27371403   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

