




PRODUCT-DETAILS

OTP125BA6M

OTP125BA6M Enclosed Switch Disconnecter



| General Information | |
|-----------------------|--|
| Extended Product Type | OTP125BA6M |
| Product ID | 1SCA022812R7690 |
| EAN | 6417019274928 |
| Catalog Description | OTP125BA6M Enclosed Switch Disconnector |
| Long Description | Encl. Switch Disconnecter, 6-p. 415V AC23 90A, 45kW. Plastic enclosure. IP65. RedYellow Pistol handle. Interlocked cover. Defeatable interlocking. The enclosure in the OTP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal. |

| Circular Value | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC340076D0201 |

| | |
|--|-----------------|
| RoHS Information | 1SCC340075D0201 |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Ordering

| | |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363030 |
| Country of Origin | Finland (FI) |

Popular Downloads

| | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC340015C0201 |
| Instructions and Manuals | 1SCC340002M0012 |

Dimensions

| | |
|-------------------------------|--------|
| Product Net Width | 200 mm |
| Product Net Height | 400 mm |
| Product Net Depth / Length | 140 mm |
| Product Net Weight | 3 kg |

Technical

| | |
|---|--|
| Rated Operational Current AC-22A (I _e) | (380 ... 415 V) 125 A (690 V) 125 A |
| Rated Operational Current AC-23A (I _e) | (380 ... 415 V) 90 A (500 V) 70 A (690 V) 50 A |
| Rated Operational Power AC-23A (P _e) | (380 ... 415 V) 45 kW (500 V) 45 kW (690 V) 45 kW |
| Conventional Thermal Current (I _{the}) | Fully Enclosed 125 A |
| Rated Insulation Voltage (U _i) | acc. to IEC/EN 60664-1 750 V |
| Rated Operational Voltage | Main Circuit 750 V |
| Rated Short-Circuit Making Capacity (I _{cm}) | (690 V AC) 3.6 kA |
| Rated Short-time Withstand Current Low Voltage (I _{cw}) | for 1 s 2.5 kA |
| Power Loss | at Rated Operating Conditions per Pole 6.3 W |
| Pollution Degree | 3 |
| Handle Color | Red / Yellow |
| Handle Type | Pistol handle |
| Standards | IEC 60947-1, -3 |
| Number of Poles | 6 |
| Neutral Type | Fixed neutral |
| Connecting Capacity Main Circuit | Screw Clamp 10 ... 70 mm ² Screw Clamp / PE Terminal 4pc,10 ... 70 mm ² |
| Cable Cross-Section | 10 ... 70 mm ² |

| | |
|------------------------------------|------------------------|
| Wire Stripping Length | 20 mm |
| Recommended Screw Driver | Main Circuit Hexagon 4 |
| Cable Entry Position | Top and/or Bottom |
| Cable Outlets Per Side | 2xM50+M16 / 2xM50+M16 |
| Degree of Protection | acc. to IEC 60529 IP65 |
| Impact Resistance Rating | Housing IK08 |
| Enclosure Material | Plastic |
| Maximum Mounted Auxiliary Contacts | 2 NO, 2 NC |
| Mounted Auxiliary Contacts | 0 NO, 0 NC |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Tightening Torque | Main Circuit 6 N·m |

Technical UL/CSA

| | |
|--------------------------|------------------------|
| Wire Stripping Length | 20 mm |
| Recommended Screw Driver | Main Circuit Hexagon 4 |
| Tightening Torque | Main Circuit 6 N·m |

Environmental

| | |
|-------------------------------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 1SCC340095D0201 |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| BV Certificate | 1SCC340018D0204 |
| Declaration of Conformity - CE | 1SCC340003D2704 |
| DNV GL Certificate | 1SCC340045D0203 |
| REACH Declaration | 1SCC340076D0201 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 213 mm |
| Package Level 1 Depth / Length | 417 mm |
| Package Level 1 Height | 197 mm |
| Package Level 1 Gross Weight | 3.2 kg |
| Package Level 1 EAN | 6417019274928 |

Classifications

| | |
|-----------------------|---|
| Object Classification | Q |
|-----------------------|---|

| | |
|---------------|--|
| Code | |
| ETIM 7 | EC000216 - Switch disconnect |
| ETIM 8 | EC000216 - Switch disconnect |
| ETIM 9 | EC000216 - Switch disconnect (low voltage) |
| eClass | V11.1 : 27371403 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

