



PRODUCT-DETAILS

OVR T2 3L 40-350 P TS QS

OVR T2 3L 40-350 P TS QS Surge Protective Device



General Information

Extended Product Type	OVR T2 3L 40-350 P TS QS
Product ID	2CTB803883R2500
EAN	3660308519856
Catalog Description	OVR T2 3L 40-350 P TS QS Surge Protective Device
Long Description	OVR T2 3L 40-350 P TS QS Surge Protective Device

Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TN-C
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U _r)	230 V AC
Nominal AC Voltage of the System (U _o)	230 / 400 V
Voltage Rating DC	420 V
Voltage Protection Level (U _p)	1.5 kV (L-N) 1.5 kV
Maximum Continuous Operating Voltage (U _c)	(L-PE) 350 V

Temporary Overvoltage Test Value (U _T)	462 V
Rated Service Short-Circuit Breaking Capacity (I _{cs})	100 kA
Discharge Current	Nominal (8 / 20 μs) 20 kA I (max, 8 / 20 μs) 40 kA
Impulse Current	I (imp, 10 / 350 μs) 2 kA
Short Circuit Withstand I _{cc}	100 kA
Arrester Class	II
Number of Protected Poles	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	3
Number of Conductors	3
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Residential, commercial building.
Auxiliary Circuit Load	Minimum 12Vdc - 10mA Maximum 250Vac - 1A
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	3 modular spacing

Material Compliance

RoHS Information	9AKK108466A4410
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20220317
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Dimensions

Width in Number of Modular Spacings	3
Product Net Width	53.4 mm
Product Net Height	95 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.36 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	375 g

Certificates and Declarations

CB Certificate	2CTC432057G1701
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410

Installation

Instructions and Manuals	2CTC432096M1701
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CTC432235D0201
Mechanical Drawings	2CTC800021F0800.pdf 2CTC800021F0801.dxf 2CTC800021F0802.stp 2CTC800021F0803.igs

Classifications

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141DDC

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II

