



PRODUCT-DETAILS

OVR T1-T2 N 100-255 C

OVR T1-T2 N 100-255 C Surge Protective Device



General Information	
Extended Product Type	OVR T1-T2 N 100-255 C
Product ID	2CTB813012R2300
EAN	4053546053319
Catalog Description	OVR T1-T2 N 100-255 C Surge Protective Device
Long Description	OVR T1-T2 N 100-255 C Cartridge for Surge Protective Device

Technical	
Standards	IEC 61643-11 EN 61643-11 UL 1449 5thEd
Type of Low Voltage Distribution System	TT TN-S
Nominal AC Voltage of the System (U _o)	233 ... 400 V
Maximum Continuous Operating Voltage (U _c)	(L-PE) - V (L-N) - V (N-PE) 255 V
Temporary Overvoltage	(N-PE) 1200/200ms V

Test Value (U _T)	
Rated Service Short-Circuit Breaking Capacity (I _{cs})	100 kA
Discharge Current	Nominal (8 / 20 μs) 25 kA I (max, 8 / 20 μs) 60 kA I (total, 10 / 350 μs) 100 kA
Impulse Current	I (imp, 10 / 350 μs) - kA I (total, 10 / 350 μs) 100 kA
Short Circuit Withstand I _{cc}	100 kA
Follow Current Extinction Capacity If (I _{fi})	(N-PE) 50 kA
Frequency (f)	45...65 Hz
Short-Circuit Protective Devices	gG Type Fuses 315 A
Arrester Class	I II
Number of Protected Poles	1
Number of Poles	1
Version	Plug-in
Mounting Type	DIN-Rail
Number of Batteries	0

Material Compliance

RoHS Information	9AKK108467A9302
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20230322
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -40 ... +70 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Technical UL/CSA

Maximum Continuous Operating Voltage UL/CSA (MCOV)	(L-PE) - V (L-L) - V (L-N) - V (N-PE) 255 V
Type of Low Voltage Distribution System UL/CSA	Single Phase

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	36 mm

Product Net Height	45 mm
Product Net Depth / Length	61 mm
Product Net Weight	0.150 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.182 kg

Certificates and Declarations

Declaration	9AKK108467A9390
Declaration of Conformity - CE	9AKK108467A9302
UL Certificate	9AKK108468A0504

Installation

Instructions and Manuals	9AKK108467A8844
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108467A6303
Mechanical Drawings	9AKK108467A9591 9AKK108467A8852

Classifications

ETIM 8	EC001457 - Combined arrester for power supply systems
ETIM 9	EC001457 - Combined arrester for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363090
UNSPSC	39-12-16-01
eClass	V11.0 : 27130808

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class I

