




PRODUCT-DETAILS

# OXB1600E3X2QB

## OXB1600E3X2QB AUTOMATIC TRANSFER SWITCH




---

### General Information

Extended Product Type	OXB1600E3X2QB
Product ID	1SCA153625R1001
EAN	6417019846514
Catalog Description	OXB1600E3X2QB AUTOMATIC TRANSFER SWITCH

**Long Description**

The all-new TruONE is the world's first true purpose-built automatic transfer switch, engineered to incorporate switch and controller in one seamless unit. Performance tested beyond standard requirements, TruONE stands ready to ensure the steady delivery of critical power at all times. Its self-contained design reduces the number of wires and connections, which speeds installation and minimizes the potential for connection failures to ensure best-in-class reliability. Its predictive maintenance and modular components reduce downtime and service costs. And its advanced connectivity is ready for the future. Every TruONE features a wide voltage range from 200 to 480 VAC (with +/-20% tolerance), reducing the need to stock multiple SKUs, reducing inventory and saving space in the warehouse. Main characteristics of this particular TruONE type: Open style ATS, delayed transition type I-O-II operation, Level 2 controller (DIP)

---

### Circular Value

Conflict Minerals Reporting Template	9AKK108467A5658
--------------------------------------	-----------------

(CMRT)

Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
REACH Declaration	1SCC011022D0201
RoHS Information	1SCC011023D0201
Toxic Substances Control Act - TSCA	1SCC303119D0201

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC303008C0201
Instructions and Manuals	1SCC303011M0201_FW2.01 1SCC303011M0201_FW2.02
Mechanical Drawings	OX_800U-1600E_3X2_B_.stp 1SCC308269F0001 1SCC308268F0001 1SCC308181F0001 1SCC308180F0001 1SCC308329F0001 1SCC308328F0001
Wiring Diagram	Circuit diagram_OXB_B_.dxf Circuit diagram_OXB_B_.pdf

### Dimensions

Product Net Width	597 mm 23.5 in
Product Net Height	359 mm 14.13 in
Product Net Depth / Length	212 mm 8.35 in
Product Net Weight	31.14 kg 68.65 lb

### Technical

Rated Operational Current AC-31B ( $I_g$ )	(200 ... 415 V AC) 1600 A
Rated Operational Current AC-32B ( $I_g$ )	(200 ... 415 V AC) 1500 A
Rated Operational Current AC-33B ( $I_g$ )	(200 ... 415 V AC) 1250 A
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40 \text{ }^\circ\text{C}$ 1600 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	Main Circuit 200 ... 480 V AC
Rated Frequency (f)	Main Circuit 50-60 Hz
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 0.1 s 65 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 49 W

Pollution Degree	3
Handle Type	Direct mounted handle
Position of Line Terminals	Supplies on Bottom - Load on Top
Standards	IEC60947-6-1
Controller Type	Level 2 (DIP)
Special Functions	Open style
Number of Poles	3
Degree of Protection	Front IP20
Terminal Type	Bolt
Transition Type	Delayed

---

### Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC303119D0201

---

### Certificates and Declarations

Declaration of Conformity - CE	1SCC303063D2701
REACH Declaration	1SCC011022D0201

---

### Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	430 mm 16.93 in
Package Level 1 Depth / Length	690 mm 27.17 in
Package Level 1 Height	450 mm 17.72 in
Package Level 1 Gross Weight	44.14 kg 97.31 lb
Package Level 1 EAN	6417019846514

---

### Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

### Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Automatic Transfer Switches TruONE

