



PRODUCT-DETAILS

PRCSSS54/25M
STNL.STL BRD.MODF.PA6 NC54 25MT BLK



General Information	
Extended Product Type	PRCSSS54/25M
Product ID	7TCA296100R0127
EAN	5020963028304
Catalog Description	STNL.STL BRD.MODF.PA6 NC54 25MT BLK
Long Description	Standard Weight Conduit, Nominal Conduit Size 54mm, NW Conduit Size 48, Coarse Conduit Pitch, Outside Diameter 42.5mm, Inside Diameter 35.1mm, Static Bend Radius 90mm, Reel Length 25 Meters, Modified Polyamide (Nylon) 6 with Stainless Steel Overbraid, Black

Additional Information	
Application	Indoors, Public Areas, Rail Infrastructure
Product Type	Standard Weight Conduit with Coarse Pitch and Stainless Steel Overbraid

Ordering	
EAN	5020963028304
UPC	786210243665

Dimensions	
Product Net Depth / Length	25 m

Technical	
Number of Batteries	0
Color	Black
Material	Modified Polyamide/Nylon 6 with Stainless Steel Overbraid

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	32.28 in 820 mm
Package Level 1 Width	32.28 in 820 mm

Certificates and Declarations	
Data Sheet, Technical Information	PRCSSS54/25M
Instructions and Manuals	PRCSSS54/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
RoHS Date	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications	
ETIM 8	EC001175 - Corrugated plastic hose
UNSPSC	39131706

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

