



PRODUCT-DETAILS

# S12/50M

## GALV.STEEL S SUPERFLEX NC12 50MT



| General Information   |                                                                                                                                                                                                      |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | S12/50M                                                                                                                                                                                              |
| Product ID            | 7TCA296010R0024                                                                                                                                                                                      |
| EAN                   | 5020963003394                                                                                                                                                                                        |
| Catalog Description   | GALV.STEEL S SUPERFLEX NC12 50MT                                                                                                                                                                     |
| Long Description      | Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 50 Meters, Galvanised Steel General Purpose |

| Additional Information |                                                  |
|------------------------|--------------------------------------------------|
| Application            | Indoors / Outdoors - Light Industrial, Buildings |
| Product Type           | Low Fire Hazard Conduit                          |

| Ordering |               |
|----------|---------------|
| EAN      | 5020963003394 |
| UPC      | 786210261133  |

| Dimensions                 |      |
|----------------------------|------|
| Product Net Depth / Length | 50 m |

| Technical           |                  |
|---------------------|------------------|
| Number of Batteries | 0                |
| Material            | Galvanized Steel |

| Environmental |                           |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information          |                 |
|--------------------------------|-----------------|
| Package Level 1 Units          | 1 piece         |
| Package Level 1 Height         | 6 in<br>152 mm  |
| Package Level 1 Depth / Length | 13 in<br>330 mm |
| Package Level 1 Width          | 13 in<br>330 mm |

| Certificates and Declarations     |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | S12/50M         |
| Instructions and Manuals          | S12/50M         |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| RoHS Information                  | 9AKK107992A8994 |
| RoHS Date                         | 9AKK107992A8994 |
| REACH Declaration                 | 9AKK107992A8994 |

| Classifications |                                     |
|-----------------|-------------------------------------|
| ETIM 8          | EC001179 - Protective metallic hose |
| UNSPSC          | 39131706                            |

---

**Categories**

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

